

RF AMPLIFIER

MODEL *TM3024*

Available as: TM3024, 4 Pin TO-8 (T4)
 TN3024, 4 Pin Surface Mount (SM3)
 FP3024, 4 Pin Flatpack (FP4)
 BX3024, Connectorized Housing (H1)

Features

- Medium Gain: 16.5 dB Typical
- Low Noise Figure: <1.75 dB Typical
- Operating Temp. -55 °C to + 85 °C
- Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	100 - 200 MHz	100 - 200 MHz
Gain (dB)	16.5	16.0 Min.
Power @ 1 dB Comp. (dBm)	+13	+11 Min.
Reverse Isolation (dB)	-18.5	-17 Max.
VSWR In	<1.3:1	2.5:1 Max.
Out	<1.5:1	2.5:1 Max.
Noise Figure (dB)	<1.75	2.5 Max.
Power Vdc	+15	+15
mA	23	26 Max.

Note: Care should always be taken to effectively ground the case of each unit.


Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point +44 dBm (Typ.)
 Second Order Two Tone Intercept Point +38 dBm (Typ.)
 Third Order Two Tone Intercept Point +27 dBm (Typ.)

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 18 Volts
 Continuous RF Input Power + 13 dBm
 Short Term RF Input Power 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.5 Watt (3 µsec Max.)

Typical Performance Data



Legend ——— + 25 °C - - - + 85 °C ······ -55 °C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 05/13/04

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001