


High Brightness LED Power Module



22140



22139

DESCRIPTION

The VLSL42xxA are metal core based high brightness LED power modules, assembled with 12, 24 or 36 HB white LEDs. The color temperature is typ. 3500 K warm white. The modules are designed for flexible use due to the option for using special reflectors to adjust the emission characteristics.

PRODUCT GROUP AND PACKAGE DATA

- Product group: LED
- Package: LED module
- Product series: power
- Angle of half intensity: $\pm 80^\circ$

FEATURES

- Metal core PCB: Al > 0.75 thickness
- Single side/single layer PCB
- Shiny white surface
- 12, 24 or 36 LED's minimum 61 lm at 350 mA per LED. Max. current per LED 1 A
- Conductive top layer: Cu (min. 18 μm)
- Isolation layer prepreg > 63 μm
- Standard solder mask material
- Compliant to RoHS Directive 2002/95/EC
- ESD withstand voltage: up to 2 kV according to JESD22-A114-B



APPLICATIONS

- Streetlight
- Internal lighting in buildings
- Tunnel lights
- General lighting application

PARTS TABLE

PART	COLOR	LUMINOUS FLUX (at $I_F = 700 \text{ mA typ.}$)	COLOR TEMPERATURE K	TECHNOLOGY
VLSL4212A	Warm white	$\Phi_V = 1500 \text{ lm}$	3500 (typ.)	InGaN
VLSL4224A	Warm white	$\Phi_V = 3000 \text{ lm}$	3500 (typ.)	InGaN
VLSL4236A	Warm white	$\Phi_V = 4500 \text{ lm}$	3500 (typ.)	InGaN

ABSOLUTE MAXIMUM RATINGS ($T_{\text{amb}} = 25^\circ\text{C}$, unless otherwise specified) VLSL4212A, VLSL4224A, VLSL4236A

PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Forward current	Per row	I_F	750	mA
Power dissipation VLSL4212A	Total (max.)	P_{tot}	35	W
Power dissipation VLSL4224A		P_{tot}	69	W
Power dissipation VLSL4236A		P_{tot}	104	W
Junction temperature		T_j	120	$^\circ\text{C}$
Operating temperature range		T_{amb}	- 40 to + 85	$^\circ\text{C}$
Storage temperature range		T_{stg}	- 40 to + 85	$^\circ\text{C}$

** Please see document "Vishay Material Category Policy": www.vishay.com/doc?99902

OPTICAL AND ELECTRICAL CHARACTERISTICS ⁽¹⁾ ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) VLSL4212A, WARM WHITE

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous flux per row ⁽²⁾	$I_F = 700\text{ mA}$	Φ_V	550	750	-	lm
Luminous flux total ⁽²⁾	$I_{board} = 2 \times 700\text{ mA}$	Φ_V	1100	1500	-	lm
Color temperature	$I_F = 700\text{ mA}$	TK	-	3500	-	K
Forward voltage per row	$I_F = 700\text{ mA}$	V_F	19	21	23	V
Class A ($V_{Fmax.} - V_{Fmin.}$) all rows ⁽³⁾	$I_F = 700\text{ mA}$	ΔV_F	-	-	0.9	V
Temperature coefficient of V_F per row	$I_F = 350\text{ mA}$	TC_{V_F}	-	- 20	-	mV/K
Temperature coefficient of Φ_V per row	$I_F = 350\text{ mA}$	TC_{Φ_V}	-	- 0.4	-	%/K

Notes

- (1) Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of $\pm 0.1\text{ V}$. Luminous flux is measured at a current pulse duration of 25 ms and an accuracy of $\pm 11\%$.
 (2) Calculated based on single LED unit.
 (3) V_F classes are marked at the LED cluster and represent the technical classification only. The single groups cannot be specifically ordered.

OPTICAL AND ELECTRICAL CHARACTERISTICS ⁽¹⁾ ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) VLSL4224A, WARM WHITE

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous flux per row ⁽²⁾	$I_F = 700\text{ mA}$	Φ_V	550	750	-	lm
Luminous flux total ⁽²⁾	$I_{board} = 4 \times 700\text{ mA}$	Φ_V	2200	3000	-	lm
Color temperature	$I_F = 700\text{ mA}$	TK	-	3500	-	K
Forward voltage per row	$I_F = 700\text{ mA}$	V_F	19	21	23	V
Class A ($V_{Fmax.} - V_{Fmin.}$) all rows ⁽³⁾	$I_F = 700\text{ mA}$	ΔV_F	-	-	0.9	V
Temperature coefficient of V_F per row	$I_F = 350\text{ mA}$	TC_{V_F}	-	- 20	-	mV/K
Temperature coefficient of Φ_V per row	$I_F = 350\text{ mA}$	TC_{Φ_V}	-	- 0.4	-	%/K

Notes

- (1) Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of $\pm 0.1\text{ V}$. Luminous flux is measured at a current pulse duration of 25 ms and an accuracy of $\pm 11\%$.
 (2) Calculated based on single LED unit.
 (3) V_F classes are marked at the LED cluster and represent the technical classification only. The single groups cannot be specifically ordered.

OPTICAL AND ELECTRICAL CHARACTERISTICS ⁽¹⁾ ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) VLSL4236A, WARM WHITE

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous flux per row ⁽²⁾	$I_F = 700\text{ mA}$	Φ_V	550	750	-	lm
Luminous flux total ⁽²⁾	$I_{board} = 6 \times 700\text{ mA}$	Φ_V	3300	4500	-	lm
Color temperature	$I_F = 700\text{ mA}$	TK	-	3500	-	K
Forward voltage per row	$I_F = 700\text{ mA}$	V_F	19	21	23	V
Class A ($V_{Fmax.} - V_{Fmin.}$) all rows ⁽³⁾	$I_F = 700\text{ mA}$	ΔV_F	-	-	0.9	V
Temperature coefficient of V_F per row	$I_F = 350\text{ mA}$	TC_{V_F}	-	- 20	-	mV/K
Temperature coefficient of Φ_V per row	$I_F = 350\text{ mA}$	TC_{Φ_V}	-	- 0.4	-	%/K

Notes

- (1) Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of $\pm 0.1\text{ V}$. Luminous flux is measured at a current pulse duration of 25 ms and an accuracy of $\pm 11\%$.
 (2) Calculated based on single LED unit.
 (3) V_F classes are marked at the LED cluster and represent the technical classification only. The single groups cannot be specifically ordered.



SPECIFICATION OF SINGLE LEDs USED FOR THE MODULES

LUMINOUS FLUX CLASSIFICATION FOR THE SINGLE LED AT 350 mA		
GROUP STANDARD	LUMINOUS FLUX Φ_v (mlm) CORRELATION TABLE	
	MIN.	MAX.
JZ	61 000	71 000
KX	71 000	82 000
KY	82 000	97 000
KZ	97 000	112 000

COLOR RANGE AND COLOR BINNING

VLSL4212A, VLSL4224A, VLSL4236A; color groups




Fig. 1 - Chromaticity Coordinates of Colorgroups


CHROMATICITY COORDINATED GROUPS FOR WHITE SMD LED										
GROUP	X	Y		GROUP	X	Y		GROUP	X	Y
40	0.386	0.361		4P	0.394	0.365		4Q	0.403	0.369
	0.389	0.369			0.398	0.373			0.406	0.377
	0.398	0.373			0.406	0.377			0.415	0.381
	0.394	0.365			0.403	0.369			0.411	0.373
50	0.389	0.369		5P	0.398	0.373		5Q	0.406	0.377
	0.392	0.377			0.401	0.381			0.410	0.386
	0.401	0.381			0.410	0.386			0.419	0.390
	0.398	0.373			0.406	0.377			0.415	0.381
60	0.392	0.377		6P	0.401	0.381		6Q	0.410	0.386
	0.394	0.385			0.404	0.390			0.413	0.394
	0.404	0.390			0.413	0.394			0.422	0.399
	0.401	0.381			0.410	0.386			0.419	0.390
70	0.394	0.385		7P	0.404	0.390		7Q	0.413	0.394
	0.397	0.393			0.407	0.398			0.416	0.403
	0.407	0.398			0.416	0.403			0.426	0.408
	0.404	0.390			0.413	0.394			0.422	0.399
80	0.397	0.393		8P	0.407	0.398		8Q	0.416	0.403
	0.400	0.401			0.410	0.406			0.420	0.412
	0.410	0.406			0.420	0.412			0.430	0.417
	0.407	0.398			0.416	0.403			0.426	0.408
90	0.400	0.401		9P	0.410	0.406		9Q	0.420	0.412
	0.402	0.410			0.413	0.415			0.423	0.420
	0.413	0.415			0.423	0.420			0.434	0.425
	0.410	0.406			0.420	0.412			0.430	0.417

VLSL4212A, VLSL4224A, VLSL4236A




Vishay Semiconductors High Brightness LED Power Module


PCB BASIC DESIGN VLSL4224A Dimensions in millimeters



Not indicated tolerances ± 0.15



Drawing-No.: 9.920-6726.02-4
 Issue:1; 11.05.10
 22136



Assembled with all jumpers. Jumpers can be removed according driver design



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.