



2000-8000 MHz

Part Number	Channels	Isolation (dB)	Insertion Loss (dB) (maximum)	Amplitude Balance (dB) (maximum)	Phase Balance (Degrees) (maximum)	VSWR In (maximum)	VSWR Out (maximum)
XMAPD10-2-8-2S	2	20	0.6	0.5	5	1.2:1	1.3:1
XMAPD10-2-8-3S	3	20	0.7	0.5	5	1.3:1	1.3:1
XMAPD10-2-8-4S	4	20	0.7	0.5	5	1.2:1	1.2:1
XMAPD10-2-8-6S	6	20	0.8	0.6	5	1.3:1	1.3:1
XMAPD10-2-8-8S	8	20	0.8	0.6	5	1.3:1	1.3:1

8000-18000 MHz

Part Number	Channels	Isolation (dB)	Insertion Loss (dB) (maximum)	Amplitude Balance (dB) (maximum)	Phase Balance (Degrees) (maximum)	VSWR In (maximum)	VSWR Out (maximum)
XMAPD10-8-18-2S	2	17	0.8	0.5	5	1.3:1	1.4:1
XMAPD10-8-18-3S	3	17	0.9	0.5	5	1.4:1	1.4:1
XMAPD10-8-18-4S	4	17	0.9	0.5	5	1.3:1	1.4:1
XMAPD10-8-18-4S	6	17	1.0	0.6	5	1.4:1	1.4:1
XMAPD10-8-18-4S	8	17	1.0	0.6	5	1.3:1	1.3:1

***Optional Connectors**

S=SMA	N=Type	B=BNC	T=TNC	D=Din	DP=Drop In
-------	--------	-------	-------	-------	------------

Some connector configurations may not be available. Please contact XMA with specifications

Specifications subject to change without notice.