


TO-264



Pin Definition:

1. Gate
2. Collector
3. Emitter

PRODUCT SUMMARY

V_{CES} (V)	V_{GES} (V)	I_C (A)
1200	±20	40

General Description

The TSG40N120CE using proprietary trench design and advanced NPT technology, the 1200V NPT IGBT offers superior conduction and switching performances, high avalanche ruggedness and easy parallel operation. This device is well suited for the resonant or soft switching application such as induction heating, microwave oven, etc.


Features

- 1200V NPT Trench Technology
- High Speed Switching
- Low Conduction Loss

Ordering Information

Part No.	Package	Packing
TSG40N120CE C0	TO-264	25pcs / Tube

Block Diagram



NPT Trench IGBT

Absolute Maximum Rating ($T_A=25^{\circ}C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit	
Collector-Emitter Voltage	V_{CES}	1200	V	
Gate-Emitter Voltage	V_{GES}	±20	V	
Continuous Current	I_C	$T_C=25^{\circ}C$	64	A
		$T_C=100^{\circ}C$	40	A
Pulsed Collector Current *	I_{CM}	120	A	
Diode Forward Current ($T_C=100^{\circ}C$)	I_F	40	A	
Diode Pulse Forward Current	I_{FM}	240	A	
Max Power Dissipation	P_D	$T_J=25^{\circ}C$	208	W
		$T_J=100^{\circ}C$	83	
Operating Junction Temperature	T_J	-55 to +150	$^{\circ}C$	
Storage Temperature Range	T_{STG}	-55 to +150	$^{\circ}C$	

* Repetitive rating; Pulse width limited by max. junction temperature

Thermal Performance

Parameter	Symbol	Limit	Unit
Thermal Resistance - Junction to Case	IGBT	0.6	°C/W
	DIODE	2.2	
Thermal Resistance - Junction to Ambient	$R\theta_{JA}$	25	

Electrical Specifications (T_C=25°C unless otherwise noted)


Parameter	Conditions	Symbol	Min	Typ	Max	Unit	
Static							
Collector-Emitter Breakdown Voltage	V _{GE} = 0V, I _C = 1mA	BV _{CES}	1200	--	--	V	
Zero Gate Voltage Collector Current	V _{CE} = 1200V, V _{GE} = 0V	I _{CES}	--	--	1	mA	
Gate-Emitter Leakage Current	V _{GE} = 20V, V _{CE} = 0V	I _{GES}	--	--	±250	nA	
Gate-Emitter Threshold Voltage	V _{GE} = V _{CE} , I _C = 40mA	V _{GE(TH)}	4.0	6.0	8.0	V	
Collector-Emitter Saturation Voltage	V _{GE} = 15V, I _C = 40A, T _J = 25°C	V _{CE(SAT)}	--	2	2.8	V	
	V _{GE} = 15V, I _C = 40A, T _J = 125°C	V _{CE(SAT)}	--	2.5	--	V	
Dynamic							
Input Capacitance	V _{CE} = 30V, V _{GE} = 0V, f = 1.0MHz	C _{IES}	--	5150	--	pF	
Output Capacitance		C _{OES}	--	150	--		
Reverse Transfer Capacitance		C _{RES}	--	100	--		
Switching							
Turn-On Delay Time	V _{CC} = 600V, I _C = 40A, R _G = 5Ω, V _{GE} = 15V Inductive Load, T _J = 25°C	t _{d(on)}	--	41	--	nS	
Rise Time		t _r	--	82	--		
Turn-Off Delay Time		t _{d(off)}	--	200	--		
Fall Time		t _f	--	85	170		
Turn-On Switching Loss		Inductive Load, T _J = 25°C	E _{on}	--	5.8	8.7	mJ
Turn-Off Switching Loss			E _{off}	--	1.5	2.3	
Total Switching Loss			E _{ts}	--	7.3	11	
Turn-On Delay Time		V _{CC} = 600V, I _C = 40A, R _G = 5Ω, V _{GE} = 15V Inductive Load, T _J = 125°C	t _{d(on)}	--	45	--	nS
Rise Time			t _r	--	76	--	
Turn-Off Delay Time	t _{d(off)}		--	212	--		
Fall Time	t _f		--	189	--		
Turn-On Switching Loss	Inductive Load, T _J = 125°C		E _{on}	--	5.6	5	mJ
Turn-Off Switching Loss			E _{off}	--	3.3	5	
Total Switching Loss			E _{ts}	--	8.9	13.4	
Total Gate Charge	V _{CC} = 600V, I _C = 40A, V _{GE} = 15V		Q _g	--	210	315	nC
Gate-Emitter Charge			Q _{ge}	--	50	75	
Gate-Collector Charge		Q _{gc}	--	115	173		

Electrical Specifications of the DIODE ($T_c=25^\circ\text{C}$ unless otherwise noted)


Parameter	Conditions		Symbol	Min	Typ	Max	Unit
Diode Forward Voltage	$I_F = 40\text{A}$,	$T_J=25^\circ\text{C}$	V_{FM}	--	2.8	--	V
		$T_J=125^\circ\text{C}$		--	2.9	--	V
Reverse Recovery Time	$I_F = 40\text{A}$, $di/dt=200\text{A}/\mu\text{s}$	$T_J=25^\circ\text{C}$	t_{fr}	--	220	--	ns
		$T_J=125^\circ\text{C}$		--	310	--	
Reverse Recovery Current		$T_J=25^\circ\text{C}$	I_{fr}	--	24	--	A
		$T_J=125^\circ\text{C}$		--	36	--	
Reverse Recovery Charge		$T_J=25^\circ\text{C}$	Q_{fr}	--	2600	--	nC
		$T_J=125^\circ\text{C}$		--	5580	--	

Electrical Characteristics Curve ($T_c = 25^\circ\text{C}$, unless otherwise noted)


Output Characteristics




Saturation voltage characteristics




Saturation voltage vs. collector current




Saturation voltage vs. gate bias



Saturation voltage vs. gate bias




Capacitance characteristics




Electrical Characteristics Curve (Ta = 25°C, unless otherwise noted)


Turn on time vs. gate resistance




Turn off time vs. gate resistance




Switching loss vs. gate resistance




Turn on time vs. collector current



Turn off time vs. collector current




Switching loss vs. collector current




Electrical Characteristics Curve ($T_c = 25^\circ\text{C}$, unless otherwise noted)


Gate charge characteristics




SOA Characteristics




RBSOA




Conduction characteristics



Conduction Characteristics




Reverse recovery current vs. forward current




Electrical Characteristics Curve ($T_c = 25^\circ\text{C}$, unless otherwise noted)


Stored recovery charge vs. forward current



Reverse recovery current vs. forward current



TO-264 Mechanical Drawing



TO-264 DIMENSION						
DIM	MILLIMETERS			INCHES		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	4.8	5.0	5.2	0.189	0.197	0.205
A1	2.5	2.8	3.1	0.098	0.110	0.122
b	0.90	1.00	1.25	0.035	0.039	0.049
b1	2.3	2.5	2.7	0.091	0.098	0.106
b2	2.8	3.0	3.2	0.110	0.118	0.126
c	0.50	0.60	0.85	0.020	0.024	0.033
D	25.58	26.09	26.59	1.007	1.027	1.047
E	19.30	19.81	20.29	0.760	0.780	0.799
e	5.15	5.45	5.75	0.203	0.215	0.226
L	19.5	20.0	20.5	0.768	0.787	0.807
L1	2.4	2.5	2.6	0.094	0.098	0.102
ΦP	3.10	3.30	3.51	0.122	0.130	0.138
Q	5.8	6.0	6.2	0.228	0.236	0.244
Q1	8.8	9.0	9.2	0.346	0.354	0.362
ΦR	--	2.0	--	--	0.079	--
$\Phi R1$	--	1.0	--	--	0.039	--

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



TSG40N120CE

N-Channel IGBT with FRD.