



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: SAW Filter 1013MHz SMD 3.0×3.0mm

TST Parts No.:TA0477A

Customer Parts No.:_____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Elvis Chiu

Approval by: _____ Francis Chen

Date: _____ 2005/06/01



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 1013 MHz

MODEL NO.: TA0477A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dB_m
2. DC voltage: 5 V
3. Operating Temperature: -30°C to 80°C
4. Storage Temperature: -40°C to +85° C



RoHS Compliant
Lead free
Lead-free soldering

B. CHARACTERISTICS:

Item				Min.	Typ.	Max.
Center frequency	Fc	MHz		-	1013	-
Insertion loss	1012.5 ~ 1013.5 MHz		dB	-	3.0	4.5
VSWR	1012.5 ~ 1013.5 MHz			-	1.5	2.3
Attenuation (Reference level from 0dB)						
	888	MHz	dB	40	50	-
	913	MHz	dB	40	50	-
	993	MHz	dB	21	40	-
	1033	MHz	dB	21	34	-
	1113	MHz	dB	40	49	-
	1138	MHz	dB	40	49	-
Source impedance	Z _S		Ω	-	50	-
Load impedance	Z _L		Ω	-	50	-



Note1. No matching network required for operation at 50Ω

C. TRANSFER FUNCTION :





REFLECTION FUNCTION:


S11




S22




D. MEASUREMENT CIRCUIT:



E. OUTLINE DRAWING:




F. PCB FOOTPRINT:



G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION

