

SPST RF SWITCH

MODEL *TWM5000*

Package: 5 Pin TO-8 (T5)
 Also Available In: Package
 and Connectorized Housings

Features

- 10 - 1500 MHz
- RF1, RF2 Terminated in "OFF" State
- Integral TTL Driver
- Absorptive
- Environmental Screening Available

Absolute Maximum (No Damage) Ratings


Ambient Operating Temperature -55°C to +100 °C
 Storage Temperature -65°C to +125 °C
 Case Temperature +125 °C
 DC Voltage +6.0 Volts
 Continuous RF Input Power +30 dBm

Specifications

CHARACTERISTIC	TYPICAL Ta = 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	10 - 1500 MHz	10 - 1500 MHz
Insertion Loss (dB)	1.2	1.7 Max.
Isolation (dB)	48	39 Min.
VSWR	1.3:1	1.7:1 Max.
DC Bias	Vdc +5 mA 2	+5 Max. 5 Max.
Switching Speed (i sec)	150	—
Transients (mV)	200	—
1dB Compression (dBm)	+23	—
Intercept Points (dBm)	IP2 +65 IP3 +40	—

Note: Care should always be taken to effectively ground the case of each unit.


Pin Layout



Truth Table

Control Input	Switch Position
TTL	RF1 to RF2
0	'OFF'
1	'ON'

Typical Performance Data



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 Rev. 5/25/10

www.SpectrumMicrowave.com Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001