



FCS-1122 Version: 1

## Megapixel PoE Network Camera

The LevelOne FCS-1122 Megapixel Network Camera is an easy-to-use surveillance system designed for business applications such as offices, banks, and retail stores. The camera features an auto-iris lens and a removable IR-cut filter to provide top quality images for day and night surveillance. An integrated IEEE 802.3af compliant PoE function makes for easy installation and negates messy cabling. Moreover, the free PC-based 64-channel monitoring software with iPhone/Android phone App within the package helps to manage multiple cameras simultaneously and offers easy mobile viewing. In addition, we offer you a free Dynamic Level1DNS™ service, which is very useful if you don't have a fixed public IP address, and provides you with an easy to memorize domain address. The FCS-1122 is an effective and cost-efficient means of surveillance for your business.



1. Status LED
2. Built-in Microphone
3. Light Sensor
4. Reset
5. Audio In
6. Audio Out
7. GPIO
8. Power Cord Socket
9. LAN Port
10. 4-pin Auto-Iris Connector

### Key Features

- Megapixel (1280 x 800) high-definition resolution
- Easy Internet monitoring via configuration free Level1DNS™ service
- IEEE 802.3af PoE compliant to simplify deployment and installation
- Digital input/output (1DI/1DO) for sensor and alarm
- Built-in microphone and external speaker for 2-way audio communication
- Removable IR-cut filter for day and night surveillance
- Supports 2 video streams simultaneously
- Dual power support: 12VDC/PoE (IEEE 802.3af)
- Built-in 4-pin auto iris lens connector
- Free 64-channel monitoring software included (supports iCamSecure App)

### Highlight

#### Free bundled 64-channel Management Software

We aim to offer you the most versatile and comprehensive surveillance solutions. Our free IP CamSecure



software coming allows you to monitor up to 64 IP cameras simultaneously on one screen to enhance scalability. For added convenience and flexibility, the software includes various advanced features such as scheduling recording, event alert, and heaps more. In addition, simply install our free iCamSecure App to your smartphone and connect to the PC with IP CamSecure software installed, you will easily turn your iPhone/Android smartphone into a portable surveillance system for real-time monitoring and snapshot.

---

## Works Well With



### **CAS-1300**

2.8 - 8.5 mm Vari-focal Day/Night Megapixel Lens



### **CAS-1400**

2.8 - 12 mm Vari-focal Day/Night 2-Megapixel Lens

---

## Specifications

### System Specifications

#### Image Sensor:

Megapixel 1/4" Progressive Scan CMOS

#### Connectors and Cabling:

1 x RJ-45 10/100 Mbps PoE port

1 x Auto Iris (DC Drive)

1 x 3.5mm line out

1 x 3.5mm mic/line in

1 x DC power jack (12V)

I/O terminal block (1 DI/1 DO)

#### Button:

Reset Button

#### Indicator:

Power/ Link

#### Lens:

C/CS-mount, fixed-focal, f=4.2 mm, F1.4

#### IR Cut Filter:

Removable infrared-cut filter for day & night function

#### Shutter Time:

1/5~1/24,500 sec.

#### Angle of View:

71°

#### Pan/Tilt/Zoom:

4x digital zoom

#### Video Compression:

H.264 / MPEG4 / MJPEG

#### Resolution:

1M (1280x800) / VGA (640x480) / CIF (320x192)

#### Video Format:

ASF

**Audio Compression:**

G.711 / AMR

**Power:**

Power Consumption: 5W

Power Input: DC12V 1A / 802.3af PoE

**Standards & Protocols:**

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, Bonjour, RTP, RTSP, RTCP

## Features

**General:**

DNS: Easy Internet monitoring via configuration free Level1DNS™ service

**Security:**

Alarm and Notification: Alarm: Motion Detection; DI/DO

Notification: HTTP, FTP, SMTP, Samba

Access Control: Multi-level user access with password protection

IP address filtering

HTTPS encrypted data transmission

**Video:**

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- ACG/AWB/AES

- Flip & Mirror

- Privacy Mask

- Time Stamp and Text Caption Overlay

Streaming: Up to 2 video streams

Motion Detection: 3 Detection Zones

**Audio:**

Streaming: 2-way audio

Input/Output: Built-in microphone

Mic/line input, line output

## Performance

**Number of Clients:**

10

**Data Transfer Rate:**

10/100Mbps

**Frame Rate:**

Up to 15 fps at 1200x800

Up to 30 fps at 640x400

**Minimum illumination:**

1 lux

## Environment

**Temperature (°C):**

Operating: 0°C ~ 50°C

**Humidity (Non-condensing):**

Operating: 10% ~ 80%



## Physical Specifications

Dimensions (W x D x H mm):

120 x 60 x 60 mm

Weight (g):

380 g

## Others

Approval and Compliance:

CE, FCC

Deployment:

Bracket for Wall/Ceiling Mount

Operation Systems:

Microsoft Windows 7/Vista/XP

Viewing System Requirements:


Browser: Internet Explorer 6.x or above

Cell phone: 3GPP player

Real Player: 10.5 or above

Quick Time 6.5 or above

## Diagram



## Order Information

FCS-1122

## Package Contents

Power Adapter

RJ45 Ethernet Cable

Stand Kit

Quick Installation Guide

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.

All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.