


JKL PART NUMBER	LENGTH A +/- 2mm	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF650-20B	50mm	RGB HIGH OUTPUT WHITE 5400° KELVIN (REF.)	390	170	5 ± 1	6,500 ± 650	20,000
BF6100-20B	100mm		500	200	5 ± 1	6,500 ± 650	20,000
BF6120-20B	120mm		590	235	5 ± 1	6,500 ± 650	20,000
BF6144-20B	144mm		600	240	5 ± 1	6,500 ± 650	20,000
BF6150-20B	150mm		615	245	5 ± 1	6,500 ± 650	20,000
BF6165-20B	165mm		640	255	5 ± 1	6,500 ± 650	20,000
BF6178-20B	178mm		675	270	5 ± 1	6,500 ± 650	20,000
BF6200-20B	200mm		725	290	5 ± 1	6,500 ± 650	20,000
BF6225-20B	225mm		825	330	5 ± 1	6,500 ± 650	20,000
BF6333-20B	333mm		1125	450	5 ± 1	6,500 ± 650	20,000

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC



THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- 0.2  
2 PL +/- 0  
ANGLE +/- 0

**JKL**

COMPONENTS CORPORATION

TITLE

SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP

A CHNG LENGTH ON BF6225-20B-220 TO 225  
RELEASED - CANCEL DRAW'S BF650-20B,  
BF696-20B, BF6100-20B & BF6150-20B

3/19/04  
2/29/00

DRAWN BY  
L. WENGSTROM

APPV'D BY DATE  
J.K. 3/19/04

SIZE  
A

FSCM NO.  
55335

DRAWING NO.

BF 6-20B

REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE

- CAD DRAWING -  
MANUAL REVISIONS NOT PERMITTED

SCALE

NONE

RELEASED DATE 2/29/00

REVISION DATE 3/19/04

REV. NO. A

SHEET 1 OF 1