



# SPN1012

## N-Channel Enhancement Mode MOSFET

### DESCRIPTION

The SPN1012 is the N-Channel enhancement mode power field effect transistors are produced using high cell density , DMOS trench technology. This high density process is especially tailored to minimize on-state resistance and provide superior switching performance. These devices are particularly suited for low voltage applications such as notebook computer power management and other battery powered circuits where high-side switching , low in-line power loss, and resistance to transients are needed.



### FEATURES

- ◆ N-Channel  
20V/0.65A,  $R_{DS(ON)}=380m\Omega@V_{GS}=4.5V$   
20V/0.55A,  $R_{DS(ON)}=450m\Omega@V_{GS}=2.5V$   
20V/0.45A,  $R_{DS(ON)}=800m\Omega@V_{GS}=1.8V$
- ◆ Super high density cell design for extremely low  $R_{DS(ON)}$
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ SOT-523 (SC-89) package design


### APPLICATIONS

- Drivers : Relays/Solenoids/Lamps/Hammers
- Power Supply Converter Circuits
- Load/Power Switching Cell Phones, Pagers

### PIN CONFIGURATION( SOT-523 / SC-89 )



### PART MARKING





# SPN1012

## N-Channel Enhancement Mode MOSFET

### PIN DESCRIPTION

Pin	Symbol	Description
1	G	Gate
2	S	Source
3	D	Drain

### ORDERING INFORMATION

Part Number	Package	Part Marking
SPN1012S52RG	SOT-523	X
SPN1012S52RGB	SOT-523	X

※ SPN1012S52RG : Tape Reel ; Pb – Free  
SPN1012S52RGB: Tape Reel ; Pb –Free, Halogen –Free

### ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit	
Drain-Source Voltage	V <sub>DSS</sub>	20	V	
Gate –Source Voltage	V <sub>GSS</sub>	±12	V	
Continuous Drain Current(T <sub>J</sub> =150°C)	I <sub>D</sub>	TA=25°C	0.65	A
		TA=80°C	0.45	
Pulsed Drain Current	I <sub>DM</sub>	1.0	A	
Continuous Source Current(Diode Conduction)	I <sub>S</sub>	0.3	A	
Power Dissipation	P <sub>D</sub>	TA=25°C	0.27	W
		TA=70°C	0.16	
Operating Junction Temperature	T <sub>J</sub>	-55/150	°C	
Storage Temperature Range	T <sub>STG</sub>	-55/150	°C	



# SPN1012

## N-Channel Enhancement Mode MOSFET

### ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)





Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	0.35		1.0	V
Gate Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 12V$			100	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=20V, V_{GS}=0V$			1	uA
		$V_{DS}=20V, V_{GS}=0V$ $T_J=55^\circ C$			5	
On-State Drain Current	$I_{D(on)}$	$V_{DS} \geq 4.5V, V_{GS}=5V$	0.7			A
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=4.5V, I_D=0.65A$		0.26	0.38	Ω
		$V_{GS}=2.5V, I_D=0.55A$		0.32	0.45	
		$V_{GS}=1.8V, I_D=0.45A$		0.42	0.80	
Forward Transconductance	$g_{fs}$	$V_{DS}=10V, I_D=0.4A$		1.0		S
Diode Forward Voltage	$V_{SD}$	$I_S=0.15A, V_{GS}=0V$		0.8	1.2	V
<b>Dynamic</b>						
Total Gate Charge	$Q_g$	$V_{DS}=10V, V_{GS}=4.5V,$ $I_D=0.6A$		1.2	1.5	nC
Gate-Source Charge	$Q_{gs}$			0.2		
Gate-Drain Charge	$Q_{gd}$			0.3		
Turn-On Time	$t_{d(on)}$	$V_{DD}=10V, R_L=10\Omega,$ $I_D=0.5A$ $V_{GEN}=4.5V, R_G=6\Omega$		5	10	ns
	$t_r$			8	15	
Turn-Off Time	$t_{d(off)}$			10	18	
	$t_f$			1.2	2.8	



# SPN1012

## N-Channel Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS









# SPN1012

## N-Channel Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS








# SPN1012

## N-Channel Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS






# SPN1012

## N-Channel Enhancement Mode MOSFET


### SOT-523 PACKAGE OUTLINE





# SPN1012

## N-Channel Enhancement Mode MOSFET



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.700	0.900	0.028	0.035
A1	0.000	0.100	0.000	0.004
A2	0.700	0.800	0.028	0.031
b1	0.150	0.250	0.006	0.010
b2	0.250	0.325	0.010	0.013
c	0.100	0.200	0.004	0.008
D	1.500	1.700	0.059	0.067
E	0.750	0.850	0.030	0.033
E1	1.450	1.750	0.057	0.069
e	0.500 TYP		0.020 TYP	
e1	0.900	1.100	0.035	0.043
L	0.550 REF		0.022 REF	
L1	0.280	0.440	0.011	0.017
θ	0°	4°	0°	4°





# SPN1012

## N-Channel Enhancement Mode MOSFET

---

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation

©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

9F-5, No.3-2, Park Street

NanKang District (NKSP), Taipei, Taiwan 115

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

©<http://www.syncpower.com>