





Verpackt im Gurt nach DIN IEC 60286-3  
 Tape on Reel Packaging according to DIN IEC 60286-3  
 Verpackungseinheit: 280 Stück  
 Packaging unit: 280 pcs



Leiterplatten-Layout Vorschlag für SMT  
 PCB-Layout Proposal for SMT




Anforderungsstufe 1  
 Performance Level 1

Kontaktbereich vergoldet  
 Mating Area gold plating

Anschlussbereich verzinkt 4-6 µm  
 Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0.1 mm  
 Coplanarity Area of Termination ≤ 0.1 mm

Abspulrichtung - Reel off Direction



BA 7-13 - 8mm Bauhöhe  
 type7-13 - Low Profile

Information:		Tolerances	 All Dimensions in mm	Scale 3:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation <b>Federl. SMC-B 50-SMD-BA7-13</b> <b>Female SMC-B 50-SMD-type7-13</b>
 www.ERNI.com		<b>154807</b>		I <b>A3</b>
e	14.01.2014	Class SMCB		
Index	Date			

Copyright by ERNI GmbH  
 Proprietary notice pursuant to ISO 16018 to be observed.