

# 4 outlets, 4-ft cord, 450 joules Protect It! Surge Suppressor

MODEL NUMBER: TLP404











#### **Highlights**

- · 4 outlets / 4-ft. cord
- 450 joule rating
- \$1000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

#### **Applications**

 Ideal for any desktop, network or home computing application requiring AC line protection

#### Package Includes

- TLP404 surge suppressor
- Instruction manual with warranty information

#### Description

Tripp Lite's TLP404 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP404 offers 4 total outlets, 4 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 450 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs and 1 designated transformer plug outlet offers convenient protection of desktop computer equipment and accessories. \$1,000 Ultimate Lifetime Insurance (USA & Canada Only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 4 NEMA5-15R/4-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/450 joules/500V UL1449 3rd Edition

#### **Features**

- 4 outlets
- 4-ft. cord
- · Surge suppression rating: 450 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Diagnostic LED confirms surge protection status
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 2 total transformers
- Keyhole supports for wall mounting
- · Lighted power switch
- \$1,000 Ultimate Lifetime Insurance (USA and Canada Only)

### **Specifications**





OUTPUT  Frequency compatibility 5  Output watts 1	Home/Office  50 / 60 Hz  1800  15  15A resettable combo switch / circuit breaker	
Frequency compatibility 5  Output watts 1	1800 15	
Output watts 1	1800 15	
	15	
Circuit Breaker (amps) 1		
Ollouit Breaker (umps)	15A resettable combo switch / circuit breaker	
Overload protection 1		
Outlet quantity / type 4	4 NEMA 5-15R	
Transformer accommodation S	Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 2 transformers total	
Outlet orientation S	Single row of 4 outlets	
INPUT		
Nominal Input Voltage(s) Supported 1	120V AC	
Recommended Electrical Service 1.	120V (110-125V)	
Input connection type N	NEMA 5-15P	
Input cord length (ft.) 4	4	
Input cord length (m) 1	1.2	
Input cord gauge, type 1	14 gauge, SJT	
Voltage compatibility (VAC)	120	
Maximum Surge Amps 2	22500	
LEDS ALARMS & SWITCHES		
Switches	Combination AC circuit breaker and 2 position on/off power switch	
Diagnostic LEDs B	Built-in LED confirms suppressor "protection present" (green) status	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating 4	450	
AC suppression response time <	< 1 ns	
Protection modes In	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS) 1	150V	
UL1449 let through rating 5	500V - UL Verified	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	





Network (Ethernet) Protection	No	
(		
PHYSICAL		
Shipping Dimensions (HWD/in)	7.72 x 3.74 x 1.02	
Shipping Dimensions (HWD/cm)	19.6 x 9.5 x 2.6	
Shipping weight (lbs)	1.2	
Shipping weight (kg)	.45	
Unit Dimensions (HWD/in)	1.2 x 1.85 x 8.1	
Unit Dimensions (HWD/cm)	3 x 4.7 x 20.6	
Unit weight (lbs)	1	
Unit weight (kg)	.45	
Material of construction	Plastic	
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting	
Housing Color	Light Gray	
Receptacle Color	Light Gray	
AC line cord color	Light Gray	
Style	Strip	
Outlets center to center measurement	28.6mm	
Keyhole slot center to center measurement	Distance between slots = 57.5mm; Distance between slot height = 26mm	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$1,000 Ultimate Lifetime Insurance	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: