

**CABLE**


single wires RADOX 155 0,5mm<sup>2</sup> BU  
 colour blue  
 ends stripped and tinned

*Einzellitzen RADOX 155 0,5mm<sup>2</sup> BU  
 Farbe blau  
 Enden abisoliert und verzinnt*

**Marking**

MEDER Label, Type  
 Production code EN60062  
 Circuit diagram

*MEDER-Logo, Typ  
 Produktionscode EN60062  
 Fertigungsstätte  
 Schaltbild*



unspecified tolerances according to DIN ISO 2768 m

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In excitation (Reference value)	Reed switch unmodified measured in coil- "define operation"	44		59	AT
Test equipment		KMS-14			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form		Form C - Changeover			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
Switching voltage	DC or Peak AC			175	V
Carry current	DC or Peak AC			1	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive			200	mOhm
Housing material		mineral-filled epoxy			
Case color		blue			

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature	cable not moved	-40		150	°C
Operating temperature	cable moved	-30		150	°C
Storage temperature		-40		150	°C

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a resistor is recommended.			
Tightening torque	Screw M3 ISO 1207 Disk ISO 7089			0,5	Nm

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Standex Electronics:](#)

[MK21M-1C90B-500W](#)