

NPN DEVICE	CASE	BREAKDOWN VOLTAGES			h _{FE}				SAT. VOLTAGES (Max.)			
		V _{CB}	V _{CE}	V _{EB}	V _{CE} (V)	I _C (A)	Min.	Max.	I _C (A)	I _B (A)	V _{CE} (V)	V _{BE} (V)
2N2106	TO-5	60	60	8	10	0.2	12	36	0.2	0.04	5	3
2N2107	TO-5	60	60	8	10	0.2	30	90	0.2	0.04	2	2
2N2108	TO-5	66	60	8	10	0.2	75	200	0.2	0.01	2	2
2N2150	TO-111	125	80	8	5	1	20	60	1	0.1	1.25	2
2N2151	TO-111	125	80	8	5	1	40	120	1	0.1	1.25	2
2N2657	TO-5	80	60	8	2	1	40	120	1	0.1	0.5	2
2N2658	TO-5	100	80	8	2	1	40	120	1	0.1	0.5	2
2N2726	TO-5	200	150	10	10	0.2	30	90	0.2	0.04	2	3
2N2727	TO-5	200	150	10	10	0.2	75	150	0.2	0.04	2	3
2N2779	TO-63	250	250	15	4	25	10		25	5	1.5	3
2N2780	TO-63	300	300	15	4	25	10		25	5	1.5	3
2N2811	TO-61	80	60	8	5	5	20	60	5	0.5	0.5	1
2N2812	TO-61	80	60	8	5	5	40	120	5	0.5	0.5	1
2N2813	TO-61	120	80	8	5	5	20	60	5	0.5	0.5	1
2N2814	TO-61	120	80	8	5	5	40	120	5	0.5	0.5	1
2N2876	TO-60	80	60	4	5	2.5	5		2.5			
2N2877	TO-111	80	60	8	2	1	20	60	1	0.1	0.25	1
2N2878	TO-111	80	60	8	2	1	40	120	1	0.1	0.25	1
2N2879	TO-111	100	80	8	2	1	20	60	1	0.1	0.25	1
2N2880	TO-111	100	80	8	2	1	40	120	1	0.1	0.25	1
2N2890	TO-5	100	80	5	2	1	30	90	1	0.2	0.75	1
2N2891	TO-5	100	80	5	2	1	50	150	1	0.2	0.75	1
2N2892	TO-111	100	80	5	2	1	30	90	1	0.2	0.75	1
2N2893	TO-111	100	80	50	2	1	50	150	1	0.2	0.75	1
2N2983	TO-5	150	80	8	5	0.5	20	60	0.5	0.1	0.6	1
2N2984	TO-5	185	120	8	5	1	20	60	1	0.4	1.25	2
2N2985	TO-5	150	80	8	5	1	40	120	1	0.4	1.25	2
2N2986	TO-5	185	120	8	5	1	40	120	1	0.4	1.25	2
2N2987	TO-5	95	80	7	5	0.2	25	75	0.2	0.02	0.8	1
2N2988	TO-5	155	100	7	5	0.2	25	75	0.2	0.02	0.8	1
2N2989	TO-5	95	80	7	5	0.2	60	120	0.2	0.02	0.8	1
2N2990	TO-5	155	100	8	5	0.2	60	120	0.2	0.02	0.8	1



