

# 10400 series

Professional pushbutton switches - threaded bushing Ø 10 (.393)

*Distinctive features and specifications*

CECC approved

## ELECTRICAL SPECIFICATIONS

- Max. current/voltage rating with resistive load :  
2A 220VAC - 3A 110VAC - 3A 24VDC
- Minimum load : 100µA 10mV
- Initial contact resistance : 10 mΩ max.
- Insulation resistance : 1.000 MΩ min. at 500VDC
- Dielectric strength :
  - 1.000 Veff. 50 Hz min. between terminals of the same pole
  - 2.000 Veff. 50 Hz min. between terminals and frame
  - 2.000 Veff. 50 Hz min. between terminals of adjacent poles
- Electrical life : 50.000 cycles

## MATERIALS

- Case : diallyphthalate (DAP)
- Actuator : brass, chrome plated
- Bushing : brass, nickel plated
- Housing : brass, nickel plated
- Contacts :
  - silver
  - gold plated silver
- Terminal seal : epoxy

## APPROVAL



CECC 96401-001

**Availability** : consult factory for details of approved models.

**Marking** : to order switches marked CECC, add "CECC" to model number.

## GENERAL SPECIFICATIONS

- Torque : 1,50 Nm (1.106 Ft.lb)  
max. applied to nut
- Operating temperature :  
-40°C to +85°C
- Max. panel thickness :  
3,5 mm (.138)

## ABOUT THIS SERIES

Complete part numbers are shown on the following page.

**Dimensions** : first dimensions are in mm while inches are shown as bracketted numbers.



**Sealing boots** are available to protect the switches against dust and water. They are presented in section H.



**Mounting accessories** : standard hardware supplied with all models : 1 knurled nut, 1 hex nut, 1 locking ring and 1 lockwasher. They are presented in section I.



**Packaging unit** : 25 pieces.

