



# DC COMPONENTS CO., LTD.

## INTEGRATED CIRCUIT

DE7808  
DE7808A

### TECHNICAL SPECIFICATIONS OF 3-Terminal Positive Voltage Regulator

#### Description


These regulators employ internal current limiting and thermal shutdown, making them essentially indestructible. They can deliver over 1A output current with adequate heatsinking. They are intended as fixed voltage regulators in a wide range of applications including local, on-card regulation for elimination of noise and distribution problems associated with single-point regulation.

#### Pinning

- 1 = Input
- 2 = Ground
- 3 = Output

#### Absolute Maximum Ratings ( $T_A=25^\circ\text{C}$ )

Characteristic	Symbol	Rating	Unit
Input Voltage	$V_I$	35	V
Total Power Dissipation	$P_D$	Internal limit	W
Operating Temperature Range	$T_{OPR}$	0 to $+125$	$^\circ\text{C}$
Maximum Junction Temperature	$T_J$	125	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 to $+150$	$^\circ\text{C}$
Lead Temperature(Soldering 10 Sec.)	$T_L$	230	$^\circ\text{C}$



#### Electrical Characteristics

( $V_{in}=14V$ ,  $I_{out}=500mA$ ,  $0^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ , unless otherwise specified)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Conditions
Output Voltage	$DE7808A$	7.76	8.00	8.24	V	$T_J=25^\circ\text{C}$
	$DE7808$	7.70	8.00	8.30		
	$DE7808A$	7.76	8.00	8.24		$P_D \leq 15W$ , $5mA \leq I_{o} \leq 1A$
	$DE7808$	7.60	8.00	8.40		
Line Regulation	$DE7808A$	-	5.0	80	mV	$T_J=25^\circ\text{C}$ , $10.5V \leq V_{in} \leq 25V$
	$DE7808$	-	5.0	160		
	$DE7808A$	-	5.0	40		$T_J=25^\circ\text{C}$ , $11.5V \leq V_{in} \leq 17V$
	$DE7808$	-	2.0	80		
Load Regulation	$DE7808A$	-	-	100	mV	$T_J=25^\circ\text{C}$ , $5mA \leq I_{o} \leq 1.5A$
	$DE7808$	-	-	160		
	$DE7808A$	-	-	50		$T_J=25^\circ\text{C}$ , $250mA \leq I_{o} \leq 750mA$
	$DE7808$	-	-	80		
Input Bias Current	$I_{IB}$	-	5.5	8.0	mA	$T_J=25^\circ\text{C}$ , $I_{o} \leq 1A$
Input Bias Current Change	$\Delta I_{IB}$	-	-	0.5	mA	$5mA \leq I_{o} \leq 1A$
		-	-	1.3		$10.5V \leq V_{in} \leq 25V$
Output Noise Voltage	$DE7808A$	-	-	200	$\mu\text{V}$	$T_A=25^\circ\text{C}$ , $10\text{Hz} \leq f \leq 100\text{KHz}$
	$DE7808$	-	-	300		
Ripple Rejection	$DE7808A$	-	68	-	dB	$11.5V \leq V_{in} \leq 21.5V$ , $f=120\text{Hz}$
	$DE7808$	62	73	-		
Dropout Voltage	$DE7808A$	-	2.0	-	V	$T_J=25^\circ\text{C}$ , $I_{o}=1A$
	$DE7808$	-	2.5	-		
Short Circuit Current	$I_{SC}$	-	1.5	-	A	$T_J=25^\circ\text{C}$
Peak Output Current	$I_{MAX}$	1.7	-	-	A	$T_J=25^\circ\text{C}$
Average $T_c$ of $V_{out}$	$\Delta V_o / \Delta T$	-	-0.8	-	$\text{mV} / ^\circ\text{C}$	$0^\circ\text{C} \leq T_J \leq +125^\circ\text{C}$ , $I_{o}=5mA$