

## Features

### General Features:

#### Architecture:

PC/104-Plus compliant

#### Video Decoder:

Conexant Fusion™ 878A (CX25878A), PC99 Compliant

#### Inputs:

4 Composite Video Inputs (1 configurable as S-Video)

#### Video Decoding Formats:

- NTSC
- PAL
- SECAM

#### Output Resolutions:

- NTSC: 640x480, 320x240, or 720x480
- PAL/ SECAM: 768x576 or 384x288

#### Acquisition Rate:

- 30 fps (NTSC)
- 25 fps (PAL / SECAM)

#### Input Formats:

- NTSC-M
- PAL-B
- PAL-G
- PAL-H
- SECAM

#### Output:

Multiple YCbCr and RGB pixel formats and YUV planar pixel formats

#### VBI Data Capture:

For Closed Caption, Teletext and Intericast Data Decoding

#### Scaling:

Horizontal & Vertical up to 16:1 in X and Y Directions

#### Filters / Scalars:

Advanced Chrominance and Luminance Comb Filters / Scalars (6-tap Luminance / 2-tap Chrominance)

#### Other Features:

- One Mono Audio Input
- Programmable Image Brightness, Contrast, Saturation and Hue
- Complex Clipping of Video Source and VGA Video Overlay

### RoHS:

- Fully RoHS (2002/95/CE) Compliant.



The INT-1462 video frame grabber is a cost-effective, high-performance solution for capturing analog broadcast signals across the PCI bus. Based around the Conexant Fusion™ 878A video decoder, this compact PC/104-Plus form factor board supports NTSC, PAL, and SECAM video formats at capture resolutions of up to 768x576 pixels and 30 frames per second. It also has the ability to sub-sample, scale, crop, and clip images at various resolutions and frame rates.

Capturing and then digitizing video in YCbCr, RGB, and YUV Planar pixel formats from up to four devices (one input channel at a time), the INT-1462 module can support four CVBS composite inputs, or three composite video and one S-Video (Y/C) input source. The board also accepts one audio input and includes 24 flexible digital I/O channels, which can be configured for digital video input, high-speed MPEG stream transport, or to input / output general board-level signals to or from the PC/104-Plus bus (for remote camera control).

Potential applications are: placing video data directly into the host memory for video capturing or into the frame buffer of a video display for video overlaying. It can also be used as a multimedia hub of an Embedded PC system connecting multiple analog and digital video sources to the CPU module via a single PCI connection. Sample applications include remote video surveillance, medical and industrial imaging, motion detection, traffic monitoring, PC / digital television, digital VCR, desktop videophone, still frame capture and VBI data service.

# INT-1462

## Applications

- Video capture
- Still frame capture
- Multimedia hub of Embedded PC system
- Mobile DVR
- Vertical blanking interval (VBI) data service

## About Eurotech

Eurotech delivers embedded computer systems for high capability and low power applications, networking and wearable computing solutions, and application framework middleware for multimedia, industrial, transportation, medical, and wireless applications. Eurotech platforms allow OEM and enterprise customers to focus on their core revenue-generating products and services and get to market quickly.

## Physical Characteristics

DIMENSIONS	90 x 96 mm (3.6" x 3.8")
POWER SUPPLY	Single +5V DC +/- 5%
POWER CONSUMPTION	1.25 W (typical)
OPERATING TEMPERATURE	0 ~ +60°C standard -40 ~ +85°C optional
HUMIDITY	Up 95% non-condensing

## Options

- Conformal Coating
- Custom Connectors
- Extended Operating Temperature Range

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.

ETH\_INT-1462\_DS221008

### Americas

**EUROTECH Inc**  
e-mail: sales-us@eurotech.com  
tel: +1 301.490.4007  
toll free: +1 888.941.2224

### Western Europe

**EUROTECH UK**  
e-mail: sales-uk@eurotech.com  
tel: +44 (0) 1223 403.410

**EUROTECH France**  
e-mail: sales-fr@eurotech.com  
tel: +33 04.72.89.00.90

### Central & Southern Europe

**EUROTECH Italy**  
e-mail: sales-it@eurotech.com  
tel: +39 0433.485.411

### Northern & Eastern Europe

**EUROTECH Finland**  
e-mail: sales-fi@eurotech.com  
tel: +358 9.477.888.0

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Eurotech:](#)

[INT-1462-00](#)