


1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
VSS	VDD	VO	C/D	RD	WR	D0	D1	D2	D3	D4	D5	D6	D7	CE	RST	VEE	MD2	FS	NC

DETAIL A:



PIN CN ASSIGNMENT	
1	CFL HOT
2	NC
3	NC
4	CFLGND

NOTES:

1. DISPLAY TYPE: STN or FSTN
2. VIEWING DIRECTION: 6:00 or 12:00
3. POLARIZER MODE: REFLECTIVE or TRANFLECTIVE
4. DRIVE METHOD: 1/128 DUTY 1/12 BIAS
5. LCD OPERATING VOLTAGE: 18.5V
6. OPERATING TEMP: NORMAL or WIDE
7. STORAGE TEMP: NORMAL or WIDE
8. BACKLIGHT TYPE: NONE, CCFL, LED, or EL
9. BEZEL IS TO BE PAINTED BLACK
10. UNMARKED TOLERANCES: ± 0.3



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM240128C	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME: TM240128CF80-1	
CONFIRMED BY:	SHEET NO: 01	