


SDS03W SDH03W SERIES

DC-DC CONVERTER

4:1 ULTRA WIDE INPUT RANGE
UP TO 3WATTS



FEATURES

- ULTRA SMALL SMD AND DIP PACKAGE, 0.52 x 0.36x 0.40 INCH WITH REGULATED
- NO MINIMUM LOAD REQUIRED
- CONTINUOUS SHORT CIRCUIT PROTECTION
- 1600VDC INPUT TO OUTPUT ISOLATION AND 3000VDC FOR OPTION
- SAFETY MEETS UL60950-1, EN60950-1, & IEC60950-1
- CE MARKED
- COMPLIANT TO RoHS II & REACH

APPLICATIONS

- WIRELESS NETWORK
- TELECOM/DATACOM
- INDUSTRY CONTROL SYSTEM
- MEASUREMENT EQUIPMENT
- SEMICONDUCTOR EQUIPMENT

3000VDC ISOLATION	1600VDC ISOLATION	REMOTE CONTROL	OCP	SCP
--------------------------	--------------------------	-----------------------	------------	------------

TECHNICAL SPECIFICATION



All specifications are typical at nominal input, full load and 25°C otherwise noted

Model Number	Input Range	Output Voltage	Output Current @Full Load	Input Current @ No Load	Efficiency	Maximum Capacitor Load
	VDC	VDC	mA	mA	%	µF
SDS(H)03-12S3P3W	4.5 ~ 18	3.3	700	35	76	4700
SDS(H)03-12S05W	4.5 ~ 18	5	600	40	80	2530
SDS(H)03-12S12W	4.5 ~ 18	12	250	40	83	1220
SDS(H)03-12S15W	4.5 ~ 18	15	200	40	84	1000
SDS(H)03-12S24W	4.5 ~ 18	24	125	40	82	470
SDS(H)03-12D05W	4.5 ~ 18	±5	±300	40	80	±1470
SDS(H)03-12D12W	4.5 ~ 18	±12	±125	40	82	±680
SDS(H)03-12D15W	4.5 ~ 18	±15	±100	40	82	±470
SDS(H)03-24S3P3W	9 ~ 36	3.3	700	20	77	4700
SDS(H)03-24S05W	9 ~ 36	5	600	20	80	2530
SDS(H)03-24S12W	9 ~ 36	12	250	25	83	1220
SDS(H)03-24S15W	9 ~ 36	15	200	25	83	1000
SDS(H)03-24S24W	9 ~ 36	24	125	25	82	470
SDS(H)03-24D05W	9 ~ 36	±5	±300	25	80	±1470
SDS(H)03-24D12W	9 ~ 36	±12	±125	25	82	±680
SDS(H)03-24D15W	9 ~ 36	±15	±100	25	82	±470
SDS(H)03-48S3P3W	18 ~ 75	3.3	700	12	77	4700
SDS(H)03-48S05W	18 ~ 75	5	600	12	80	2530
SDS(H)03-48S12W	18 ~ 75	12	250	13	83	1220
SDS(H)03-48S15W	18 ~ 75	15	200	14	83	1000
SDS(H)03-48S24W	18 ~ 75	24	125	14	82	470
SDS(H)03-48D05W	18 ~ 75	±5	±300	14	80	±1470
SDS(H)03-48D12W	18 ~ 75	±12	±125	14	82	±680
SDS(H)03-48D15W	18 ~ 75	±15	±100	14	82	±470

PART NUMBER STRUCTURE

SDS03 -	24	S	05	W	H
Series Name	Input Voltage (VDC)	Output Quantity	Output Voltage (VDC)	Input Range	Isolation Option
SDS : SMD type SDH : DIP type	12: 4.5~18 24: 9~36 48:18~75	S :Single	3P3 :3.3 05 :5 12 :12 15 :15 24 :24	4:1	<input type="checkbox"/> : 1600VDC Isolation <input type="checkbox"/> : 3000VDC Isolation
		D :Dual	05 :±5 12 :±12 15 :±15		

INPUT SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Operating input voltage range	12Vin(nom)	4.5	12	18	VDC
	24Vin(nom)	9	24	36	
	48Vin(nom)	18	48	75	
Start up time	Constant resistive load Power up Remote ON/OFF		5 5	10 10	ms
Input surge voltage	1 second, max.			25 50 100	VDC
Input reflected ripple current ⁽¹⁾	12Vin(nom)		20		mAp-p
	24Vin(nom)		20		
	48Vin(nom)		20		
Input filter			Capacitor type		
Remote ON/OFF	DC-DC ON Ctrl pin applied current via 1kΩ	Open or high impedance			mA
	DC-DC OFF Remote off input current	2.0	3.0	4.0	mA
<p>Application circuit</p> <p>DC-DC ON</p>  <p>DC-DC OFF</p> 					

OUTPUT SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Voltage accuracy		-1.0		+1.0	%
Line regulation	Low Line to High Line at Full Load	-0.2		+0.2	%
Load regulation	No Load to Full Load	Single		+1.0	%
		Dual		+1.0	
	10% Load to 90% Load	Single	-0.5		+0.5
		Dual		+0.8	
Cross regulation	Asymmetrical load 25%/100% FL	-5.0		+5.0	%
Ripple and noise	Measured by 20MHz bandwidth		50		mVp-p
Temperature coefficient		-0.02		+0.02	%/°C
Transient response recovery time	25% load step change		500		μs
Short circuit protection		Continuous, automatic recovery			

GENERAL SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Isolation voltage	1 minute	1600			VDC
		3000			
Isolation resistance	500VDC	1			GΩ
Isolation capacitance		Standard		50	pF
		Suffix "H"		50	
Switching frequency		100			kHz
Design meets					UL60950-1 EN60950-1 IEC60950-1
Case material					Non-conductive black plastic
Base material					Non-conductive black plastic
Potting material					Silicone (UL94 V-0)
Weight					2.7g (0.10oz)
MTBF	MIL-HDBK-217F, Full load				5.627 x 10 ⁶ hrs

ENVIRONMENTAL SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Operating ambient temperature	Without derating	-40		71	°C
	With derating	71		+105	
Storage temperature range		-55		+125	°C
Thermal shock					MIL-STD-810F
Vibration					MIL-STD-810F
Relative humidity					5% to 95% RH


EMC SPECIFICATIONS			
Parameter	Conditions		Level
EMI (1)	EN55022		Class A, Class B
ESD	EN61000-4-2	Air ± 8kV Contact ± 6kV	Perf. Criteria A
Radiated immunity	EN61000-4-3	10 V/m	Perf. Criteria A
Fast transient (2)	EN61000-4-4	± 2kV	Perf. Criteria A
Surge (2)	EN61000-4-5	± 1kV	Perf. Criteria A
Conducted immunity	EN61000-4-6	10 Vr.m.s	Perf. Criteria A

Note:


- The standard modules meet EMI Class A or Class B and input reflected ripple current with external components. For further information, please contact with P-DUKE.
- An external input filter capacitor is required if the module has to meet EN61000-4-4, EN61000-4-5. The filter capacitor Power Mate suggest: Nippon chemi-con KY series, 220 µF/100V.

CAUTION: This power module is not internally fused. An input line fuse must always be used.


CHARACTERISTIC CURVE



SDS(H)03-24S05W Derating Curve




SDS(H)03-24S05W Efficiency vs. Input Voltage



SDS(H)03-24S05W Efficiency vs. Output Current

MECHANICAL DRAWING

SDS03W: SMD TYPE



PIN CONNECTION

PIN	SINGLE	DUAL
1	+Vin	+Vin
2	-Vin	-Vin
4	Ctrl	Ctrl
5	NC	-Vout
6	-Vout	Common
7	+Vout	+Vout

- All dimensions in inch (mm)
- Tolerance :x.xx±0.02 (x.x±0.5)
x.xxx±0.01 (x.xx±0.25)
- Pin pitch tolerance ±0.01 (0.25)
- Pin dimension tolerance ±0.004(0.1)

SDH03W: DIP TYPE

