

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

8-Port NetDirector 1U Rackmount Console KVM Switch w/19" LCD + 8 PS2/USB Combo Cables

MODEL NUMBER: B020-U08-19-K





Description

Tripp Lite's 8-port Console KVM Switch with 19" LCD is the optimal solution for controlling multiple computers from one keyboard, mouse and monitor. This single unit combines an 8 port KVM switch, keyboard, 19" LCD monitor and touchpad; all in a mere 1U of rack space. Stores neatly in the rack, pulls out when needed. Control up to 504 computers from this single console by daisy-chaining additional 16 port KVM switches (model B022-U16). Easily switch ports using the On-Console push buttons, On Screen Display (OSD) or keyboard hot key commands. Includes eight, six foot Combo cable kits, which allow connection to either PS/2 or USB servers...no adapters needed. Includes a console cable kit that plugs into the port on the back of the unit, providing an extra HD15, (2) USB and (2) PS/2 ports that can be used to connect a Tripp Lite B051-000 IP Remote Access Unit or an external console. Two USB ports are provided on the front of the unit: One for attachment of a separate USB mouse, and the other for attachment of USB peripherals, such as a flash drive, external hard drive, etc. to be shared between connected servers. Compatible with all major operating systems. Constructed of heavy-duty steel housing.

Features

- 1U rackmount console with built-in 8-Port KVM switch, 19" LCD screen, keyboard, and touchpad
- Includes (x8) P778-Series USB/PS2 Combo KVM Cable Kits
- Additional ports are provided for the connection of an external console (PS/2 or USB) or IP remote access unit (model B051-000)
- Features a USB 1.1 port on the LCD panel for the sharing of USB peripherals such as Flash Drives and Card Readers amongst the connected computers
- Features a USB 1.1 port on the keyboard panel for the convenient connection of an external mouse
- USB/PS2 combo KVM cable kits allow you to connect to a USB or PS/2 computer without having to purchase separate cables or adapters
- Control up to 504 computers by daisychaining up to 31 additional B022-U16 KVM switches
- Daisychain station position is automatically sensed; no need for manual DIP switch settings

Highlights

- 1U Rackmount console with built-in 8-Port KVM switch, 19" LCD screen, keyboard, and touchpad
- Comes with (x8) 6 ft. USB/PS2 combo KVM cable kits
- Supports video resolutions up to 1280 x 1024
- Features an additional USB 1.1 port for sharing peripherals amongst connected computers
- OSD available in English,
 Spanish, French, German, and
 Japanese
- Compatible with all major operating systems

System Requirements

- Computer with a HD15 port, and a USB port or PS/2 keyboard/mouse ports
- P778-006 USB/PS2 combo KVM cable kit is required for each connected computer/server
- Compatible with all major operating systems

Package Includes

- B020-U08-19-K 1U rackmount console with built-in 8-Port KVM switch, 19" LCD, keyboard, and touchpad
- (x8) P778-006 6 ft. USB/PS2 combo KVM cable kits
- USB/PS2 combo console cable kit
- RJ11 to DB9 firmware upgrade
- C13 to 5-15P power cord
- CD with owner's manual
- Quick start guide
- Grounding wire
- Rackmount hardware



- OSD available in English, Spanish, French, German, and Japanese
- Switch ports via on-console pushbuttons, hotkey keyboard commands, or the OSD
- Auto scan feature allows for continuous scanning of connected computers
- Two level password security (up to four Users and one Administrator)
- Supports video resolutions up to 1280 x 1024
- Firmware upgradeable
- Input Power: 100-240VAC, 50/60Hz, 1A
- Power Consumption: 120V, 28.5W / 230V, 29.1W\
- Compatible with all major operating systems
- Constructed of heavy-duty steel housing

Specifications

| - | | | |
|-------------------------------|--|--|--|
| OVERVIEW | | | |
| # Of Users | 1 | | |
| Console | Yes | | |
| Port Control | Push Buttons, Hotkeys, OSD | | |
| Max CPU | 504 | | |
| PC/Server | PS/2 | | |
| Unit Dimensions (HWD/in.) | 1.75 x 17 x 27 | | |
| IP Remote Access | No | | |
| PHYSICAL | | | |
| Unit Dimensions (HWD/cm) | 4.45 x 43.18 x 68.58 | | |
| Unit weight (lbs) | 30.6 | | |
| Unit weight (kg) | 13.88 | | |
| Mounting accessories included | Yes | | |
| Color | Black | | |
| Style | 1U Rackmount Console | | |
| LCD Monitor (in.) | 19 | | |
| LCD Monitor (cm) | 48.26 | | |
| | | | |
| ENVIRONMENTAL | | | |
| Storage Temperature Range | -4 Degrees F to 140 degrees F (-20 to +60 C) | | |
| Relative Humidity | 0 to 80% RH, Non-condensing | | |
| Operating Temperature | 32 Degrees F to 120 Degrees F (0 to 50 C) | | |
| CONNECTIONS | | | |
| CONNECTIONS | | | |



| Ports | 8 | |
|---------------------------------------|--|--|
| Computer/Server Ports | (x8) HD18 (Female) | |
| Daisy-Chain Port | DB25 Male | |
| Firmware Upgrade Port | RJ45 | |
| Included Cable (Side A) - Connector 1 | HD18 Male | |
| Included Cable (Side B) - Connector 1 | HD15 Male | |
| Included Cable (Side B) - Connector 2 | PS/2 male | |
| Included Cable (Side B) - Connector 3 | PS/2 Male | |
| Included Cable (Side B) - Connector 4 | USB A Male | |
| Other Ports - Port 1 | USB A for Optional USB Mouse connection | |
| Other Ports - Port 2 | USB A for Optional Flash Drive connection | |
| Remote Console Port | HD18 Female + Dongle Cable Kit w/VGA, PS2, & USB Females | |
| FEATURES/SPECIFICATIONS | | |
| Autoscan (Y,N) | Y | |
| CERTIFICATIONS | | |
| Approvals | UL, cUL, CE, FCC, RoHS | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | 1-year limited warranty | |
| | | |

Related Items

Optional Products

| Model Number | Description | Qty. |
|--------------|---|------|
| B019-000 | KVM Switch Accessories - 2-Post Rackmount Bracket for B020,B021, B040, and B070 Consoles and KVM Consoles | 1 |
| P778-006 | 6-ft. KVM Switch USB/PS2 Combo Cable for B020-U08/U16 and B022-U16 KVMs | 1 |
| WEXT-KVM-B1 | 1-Year Warranty Extension - For select KVM Switches (see specific models for eligibility) | 1 |
| WEXT-KVM-B2 | 2-Year Warranty Extension - For select KVM Switches (see specific models for eligibility) | 1 |
| WEXT-KVM-B3 | 3-Year Warranty Extension - For select KVM Switches (see specific models for eligibility) | 1 |
| WEXT-KVM-B4 | 4-Year Warranty Extension - For select KVM Switches (see specific models for eligibility) | 1 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

More information, including related products, owner's manuals, and additional technical specifications, can be found online at: http://www.tripplite.com/sku/B020-U08-19-K.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:
B020-U08-19-K