

MicroPAC AC-DC Power Supply



High efficiency up to 92%

Small Size

High power density

> 25 W/In³

Up to 1,300 W

> Configuration dependent

Low power standby mode

> Green mode

Universal input

> 47 to 400 Hz

> 85 to 264 Vac

DC input

> 120 to 300 Vdc

Up to 4 isolated outputs

12 V output standard

48 V output standard

Aux isolated 5 V @ 500 mA

bias standby supply

Output parallel capability

Output series capability

Output current sharing

MicroPAC to MicroPAC

current sharing

Optional power shed capability

Over temperature warning

Over temperature shutdown

Intelligent fan control

Field replaceable fan

Individual output enable / disable

All output enables / disable

capability

TTL control signals


Visual LED display panel

Product Description

The MicroPAC is the first Westcor product to utilize Vicor's VI Chip technology. The power supply uses BCM modules to provide up to 4 isolated semi regulated output voltages of 12, 24, 36 and 48 Vdc and up to 1300 W of continuous power in a very small highly efficient package. The isolated outputs may be placed in parallel/series configurations and for applications requiring higher power levels MicroPAC power supplies can be configured in arrays up to several KW.

This factory configurable rugged power supply supports a wide range of customer power requirements and is especially suited for distributed power architectures. The design offers a small flexible cost effective solution for applications requiring Power Factor Correction, high efficiency and power density even in environmentally challenging conditions.

Part Numbering



Examples:

UP1-FZZZ-FSG Denotes a single output of 24 V 1200 W with a standard fan, standard TTL signaling and control, RoHS compliant

UP4-AAAA-LSN Denotes 4 output unit, each output is 12 V 300 W. The fan is a -40°C capable unit, standard TTL signaling, and the unit is non-RoHS

Specifications


Input		
Input Voltage	85 – 264 Vac	DC Rating: 120 Vdc – 300 Vdc
External Fuse	(¼" x 1¼") Cooper Bussmann, ABC-15, rated 15 A Littelfuse, 505 series, rated 16 A/500 Vdc	(5 x 20 mm) Littelfuse, 216 series, rated 16 A (¼" x 1¼") Littelfuse, 505 series, rated 16 A / 500 Vdc
Frequency	47 ~ 400 Hz	
Inrush Current	30 A Peak	
Efficiency	≥92% @ Full load @ 25°C ambient 48 V output	≥91% @ Full load @ 25°C ambient 12 V output
Power factor	>0.95 typ. Meets EN61000-3-2	
Turn-on time	AC on 1.5 sec TYP	
Conducted EMI	EN55022 Class B Information technology equipment — Radio disturbances characteristics — Limits and methods of measurement BS EN55022:1998; CISPR 22:1997, incorporating corrigendum	
Harmonic distortion	Meets IEC 61000-3-2	
Isolation	Meets IEC 60950	
Leakage current	< 3.5 mA @ 264 Vac @ 63 Hz	
Hold up time	20 mS typical	
Warranty	2 Years	
Output		
Number of outputs	1 to 4	
Normal output voltages	12 V, 24 V, 36 V and 48 V (contact factory for details)	
Maximum output current	100 A @ 12 V	[27 A @ 48 V]
Auxiliary output	5 V @ 0.5 A 50 mV p-p	
Voltage regulation	12 V output (11.3 V ~ 12.5 V)	48 V output (45 V ~ 50 V)
Ripple and noise (20 MHz bandwidth)	12 V output (197 mV ~ 400 mV p-p)	48 V output (1.6 Vp-p)
Current sharing accuracy	5 to 10%	
Short circuit protection	"Fold-Back" Technique	
Over voltage protection	12 V output set point 12.5 V typical	48 V modules 50 V typical
Thermal protection	All outputs disabled when internal temperature exceeds safe operating	
Maximum load	12 V up to 1200 W	
Maximum load	48 V up to 1300 W	
Maximum load	5.0 V Aux up to 2.5 W	
Maximum load capacitance	1000 µF per 12 V output	100 µF per 48 V output

Specifications (CONT.)

Environmental	
Storage temperature	-40°C ~ +85°C
Operating temperature	-20°C ~ +55°C (Extended temperature range is available; -40°C to +55°C)
Functional shock	MIL-STD 810F Method 516.5 procedure 1, terminal peak saw-tooth wave, 40G 11 mS
Vibration	Mil-STD 810G for minimum integrity vibration
Humidity	95% non condensing
Cooling	Fan cooled (field replaceable) temperature speed control
Electromagnetic Compatibility	
	EN61000-6-1n European General EMC Immunity
IEC 61000-4-11 [50 Hz]	Voltage Dips 30% for 0.5 prd, pc C Voltage Interrupts (pc C)
IEC 61000-4-4 [TRANSIENT]	EFT/Burst ± 1 kV AC leads ± 500 V DC leads. 5/50 nsec 5 kHz rep rate (pc B)
IEC 61000-4-5 [SURGE]	Power line Surge AC in ± 2 kV CM ± 1 kV DM DC in ± 500 V CM & DM 1.2/ μ Sec (pc B)
EN 61000-4-6 [0.15 to 80 MHz]	RF Common Mode Input leads, AC & DC leads, CDN 150 kHz to 80 MHz, 3 Vrms with 80% AM @1 kHz (pa A)
EN 61000-4-2 [ELECTROSTATIC]	Electrostatic Discharge ± 4 kV Contact ± 8 kV Discharge (pc B)
EN 61000-4-3	RF E-Field 80 MHz to 1 GHz 3 V/m with 80% AM @ 1 kHz (pc A)
EN 61000-4-8	Power Freq H-Field 3A/M @ 50 Hz (pa A)
Reliability	
FIT	TBD
Service life	5 Years
Safety & Regulatory	
UL	UL 60950-1:2007 CAN C22.2 No. 60950-1-07
CSA	CSA*60950 3rd Edition (CB Report to include all national deviations)
EN	EN 60950-1/A1:2010
IEC	60950-1-2005 2 Ed. +A1:2009

Mechanical Drawings

Figure 1:
Physical Dimensions
and Electrical Connections



Vicor's comprehensive line of power solutions includes high density AC-DC and DC-DC modules and accessory components, fully configurable AC-DC and DC-DC power supplies, and complete custom power systems.

Information furnished by Vicor is believed to be accurate and reliable. However, no responsibility is assumed by Vicor for its use. Vicor makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication. Vicor reserves the right to make changes to any products, specifications, and product descriptions at any time without notice. Information published by Vicor has been checked and is believed to be accurate at the time it was printed; however, Vicor assumes no responsibility for inaccuracies. Testing and other quality controls are used to the extent Vicor deems necessary to support Vicor's product warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed. Specifications are subject to change without notice.

Vicor's Standard Terms and Conditions

All sales are subject to Vicor's Standard Terms and Conditions of Sale, which are available on Vicor's webpage or upon request.

Product Warranty

In Vicor's standard terms and conditions of sale, Vicor warrants that its products are free from non-conformity to its Standard Specifications (the "Express Limited Warranty"). This warranty is extended only to the original Buyer for the period expiring two (2) years after the date of shipment and is not transferable.

UNLESS OTHERWISE EXPRESSLY STATED IN A WRITTEN SALES AGREEMENT SIGNED BY A DULY AUTHORIZED VICOR SIGNATORY, VICOR DISCLAIMS ALL REPRESENTATIONS, LIABILITIES, AND WARRANTIES OF ANY KIND (WHETHER ARISING BY IMPLICATION OR BY OPERATION OF LAW) WITH RESPECT TO THE PRODUCTS, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR REPRESENTATIONS AS TO MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, INFRINGEMENT OF ANY PATENT, COPYRIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT, OR ANY OTHER MATTER.

This warranty does not extend to products subjected to misuse, accident, or improper application, maintenance, or storage. Vicor shall not be liable for collateral or consequential damage. Vicor disclaims any and all liability arising out of the application or use of any product or circuit and assumes no liability for applications assistance or buyer product design. Buyers are responsible for their products and applications using Vicor products and components. Prior to using or distributing any products that include Vicor components, buyers should provide adequate design, testing and operating safeguards.

Vicor will repair or replace defective products in accordance with its own best judgment. For service under this warranty, the buyer must contact Vicor to obtain a Return Material Authorization (RMA) number and shipping instructions. Products returned without prior authorization will be returned to the buyer. The buyer will pay all charges incurred in returning the product to the factory. Vicor will pay all reshipment charges if the product was defective within the terms of this warranty.

Life Support Policy

VICOR'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF VICOR CORPORATION. As used herein, life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness. Per Vicor Terms and Conditions of Sale, the user of Vicor products and components in life support applications assumes all risks of such use and indemnifies Vicor against all liability and damages.

Intellectual Property Notice

Vicor and its subsidiaries own Intellectual Property (including issued U.S. and Foreign Patents and pending patent applications) relating to the products described in this data sheet. No license, whether express, implied, or arising by estoppel or otherwise, to any intellectual property rights is granted by this document. Interested parties should contact Vicor's Intellectual Property Department.

Vicor Corporation

25 Frontage Road
Andover, MA, USA 01810
Tel: 800-735-6200
Fax: 978-475-6715

Email

Customer Service: custserv@vicorpower.com
Technical Support: apps@vicorpower.com