



SPECIFICATION BULLETIN **MR140M Open Substrate Mixer**
RF: 4 to 18 GHz **IF: 1 to 10 GHz**

- Standard Product Features:**
- Surface Mount (Drop-in)
 - Triple Balanced
 - 6.0 dB Typical Conversion Loss
 - 30 dB Typical Isolation
 - IF Coverage to 10 GHz
 - LO Drive 13 to 17 dBm
 - Protective Covers



SPECIFICATIONS	TYPICAL	Min.	Max.
RF/LO Frequency Range	-----	4 GHz	18 GHz
IF Frequency Range (3 dB Bandwidth)	-----	1	10 GHz
Conversion Loss	6.0 dB	----	10.5 dB
LO Drive Level	15.0 dBm	13.0 dBm	17.0 dBm
Isolation, LO to RF	30 dB	20 dB	---
LO to IF	25 dB	15 dB	---
VSWR, RF	2.2:1	---	---
LO	1.6:1	---	---
Input 1 dB Compression	10 dBm	7 dBm	---
Input Two-Tone Third Order IP (IP3)	18 dBm	14 dBm	---
Operating Temperature Range	---	-54 C	+95 C
Storage Temperature Range	---	-65 C	+125 C

Alternate LO Drive Ranges are available. Consult factory for assistance on your requirements.

OUTLINE DRAWING

