



8LS1  
 PAGE 1 OF 1  
 M  
 DRAWING NUMBER  
 ISSUE 17  
 REVISIONS  
 A CO 15200  
 O M W  
 18 JUN 65  
 B CO 23403  
 G F S  
 26 SEPT 68  
 C CO 24612  
 R E R  
 15 OCT 68  
 D CO 25152  
 W A W  
 19 APR 69  
 E CO  
 50952-F  
 T S K  
 9 JUNE 83  
 F CO  
 53005-D  
 C J H  
 AUG 84  
 G CO  
 65814-E  
 G R T  
 26 NOV 90  
 H CO  
 77031  
 J D B  
 22 DEC 93  
 J CO 94494  
 J A F  
 19 MAR 99  
 O M W 18 JUN 65  
 DRAWN  
 FORMTEK  
 FO-80378-003

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	ELECTRICAL DATA	SCALE 1/2 TO 1
OPERATING FORCE ----- 5 OZ MAX	CONTACT ARRANGEMENT (SEE CIRCUIT DIAGRAM)	DO NOT SCALE PRINT
FORCE AT 2.0 ----- 10 OZ MAX	10A-120, 240, OR 480 VAC; 1/4 HP - 120 VAC 1/2 HP - 240 VAC; 0.8A - 115 VDC; 0.4A - 230 VDC .1A - 550 VDC PILOT DUTY: 600 VAC MAX	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES TOLERANCES ARE: ONE PLACE (.0) ± .030 TWO PLACE (.00) ± .015 THREE PLACE (.000) ± .005 ANGLES ±
SWITCH - BASIC REPLACEMENT ----- 2MN11		WEIGHT

NOTE -  
 SEAL TO BE FURNISHED BY USER