


# PolarHV™ Power MOSFET

## IXTQ 44N50P


**V<sub>DSS</sub>** = 500 V  
**I<sub>D25</sub>** = 44 A  
**R<sub>DS(on)</sub>** ≤ 140 mΩ

N-Channel Enhancement Mode  
Avalanche Rated



Symbol	Test Conditions	Maximum Ratings		
V <sub>DSS</sub>	T <sub>J</sub> = 25°C to 150°C	500	V	
V <sub>DGR</sub>	T <sub>J</sub> = 25°C to 150°C; R <sub>GS</sub> = 1 MΩ	500	V	
V <sub>GS</sub>	Continuous	±30	V	
V <sub>GSM</sub>	Transient	±40	V	
I <sub>D25</sub>	T <sub>C</sub> = 25°C	44	A	
I <sub>DM</sub>	T <sub>C</sub> = 25°C, pulse width limited by T <sub>JM</sub>	110	A	
I <sub>AR</sub>	T <sub>C</sub> = 25°C	44	A	
E <sub>AR</sub>	T <sub>C</sub> = 25°C	55	mJ	
E <sub>AS</sub>	T <sub>C</sub> = 25°C	1.7	J	
dV/dt	I <sub>S</sub> ≤ I <sub>DM</sub> , di/dt ≤ 100 A/μs, V <sub>DD</sub> ≤ V <sub>DSS</sub> , T <sub>J</sub> ≤ 150°C, R <sub>G</sub> = 10 Ω	10	V/ns	
P <sub>D</sub>	T <sub>C</sub> = 25°C	650	W	
T <sub>J</sub>		-55 ... +150	°C	
T <sub>JM</sub>		150	°C	
T <sub>stg</sub>		-55 ... +150	°C	
T <sub>L</sub>	1.6 mm (0.062 in.) from case for 10 s	300	°C	
T <sub>SOLD</sub>	Plastic body for 10 s	260	°C	
M <sub>d</sub>	Mounting torque(TO-247)	1.13/10	Nm/lb.in.	
Weight		6	g	

### TO-3P (IXTQ)



G = Gate  
S = Source

D = Drain  
TAB = Drain

### Features

- International standard packages
- Unclamped Inductive Switching (UIS) rated
- Low package inductance
  - easy to drive and to protect

### Advantages

- Easy to mount
- Space savings
- High power density

Symbol	Test Conditions (T <sub>J</sub> = 25°C, unless otherwise specified)	Characteristic Values		
		Min.	Typ.	Max.
BV <sub>DSS</sub>	V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA	500		V
V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA	3.0		5.0 V
I <sub>GSS</sub>	V <sub>GS</sub> = ±30 V <sub>DC</sub> , V <sub>DS</sub> = 0			±10 nA
I <sub>DSS</sub>	V <sub>DS</sub> = V <sub>DSS</sub> V <sub>GS</sub> = 0 V			25 μA 250 μA
R <sub>DS(on)</sub>	V <sub>GS</sub> = 10 V, I <sub>D</sub> = 0.5 I <sub>D25</sub> Pulse test, t ≤ 300 μs, duty cycle d ≤ 2 %			140 mΩ


Symbol	Test Conditions	Characteristic Values ( $T_j = 25^\circ C$ , unless otherwise specified)		
		Min.	Typ.	Max.
$g_{fs}$	$V_{DS} = 20 V$ ; $I_D = 0.5 I_{D25}$ ; pulse test	20	32	S
$C_{iss}$	$V_{GS} = 0 V$ , $V_{DS} = 25 V$ , $f = 1 MHz$	5440	pF	
$C_{oss}$		639	pF	
$C_{rss}$		40	pF	
$t_{d(on)}$	$V_{GS} = 10 V$ , $V_{DS} = 0.5 V_{DSS}$ , $I_D = I_{D25}$ $R_G = 3 \Omega$ (External)	25	ns	
$t_r$		27	ns	
$t_{d(off)}$		75	ns	
$t_f$		21	ns	
$Q_{g(on)}$	$V_{GS} = 10 V$ , $V_{DS} = 0.5 V_{DSS}$ , $I_D = 0.5 I_{D25}$	98	nC	
$Q_{gs}$		35	nC	
$Q_{gd}$		30	nC	
$R_{thjc}$	(TO-3P)	0.21	$0.19^\circ C/W$	
$R_{thcs}$			$^\circ C/W$	

## Source-Drain Diode

Characteristic Values  
( $T_j = 25^\circ C$ , unless otherwise specified)

Symbol	Test Conditions	Min.	Typ.	Max.
$I_s$	$V_{GS} = 0 V$		44	A
$I_{SM}$	Repetitive		110	A
$V_{SD}$	$I_F = I_s$ , $V_{GS} = 0 V$ , Pulse test, $t \leq 300 \mu s$ , duty cycle $d \leq 2\%$		1.5	V
$t_{rr}$	$I_F = 22 A$ $-di/dt = 100 A/\mu s$	400		ns

## TO-3P (IXTQ) Outline




1 - GATE  
2 - DRAIN (COLLECTOR)  
3 - SOURCE (EMITTER)  
4 - DRAIN (COLLECTOR)

SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.185	.193	4.70	4.90
A1	.051	.059	1.30	1.50
A2	.057	.065	1.45	1.65
b	.035	.045	0.90	1.15
b2	.075	.087	1.90	2.20
b4	.114	.126	2.90	3.20
c	.022	.031	0.55	0.80
D	.780	.799	19.80	20.30
D1	.665	.677	16.90	17.20
E	.610	.622	15.50	15.80
E1	.531	.539	13.50	13.70
e	.215 BSC		5.45 BSC	
L	.779	.795	19.80	20.20
L1	.134	.142	3.40	3.60
ØP	.126	.134	3.20	3.40
ØP1	.272	.280	6.90	7.10
S	.193	.201	4.90	5.10


IXYS reserves the right to change limits, test conditions, and dimensions.

IXYS MOSFETs and IGBTs are covered by 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 one or more of the following U.S. patents: 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405B2 6,759,692 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2


**Fig. 1. Output Characteristics  
@ 25°C**




**Fig. 2. Extended Output Characteristics  
@ 25°C**




**Fig. 3. Output Characteristics  
@ 125°C**




**Fig. 4.  $R_{DS(on)}$  Normalized to  $I_D = 22A$  Value  
vs. Junction Temperature**









**Fig. 5.  $R_{DS(on)}$  Normalized to  $I_D = 22A$  Value  
vs. Drain Current**



**Fig. 6. Maximum Drain Current vs.  
Case Temperature**



**Fig. 7. Input Admittance****Fig. 8. Transconductance****Fig. 9. Forward Voltage Drop of Intrinsic Diode****Fig. 10. Gate Charge****Fig. 11. Capacitance****Fig. 12. Forward-Bias Safe Operating Area**

**Fig. 13. Maximum Transient Thermal Resistance**