



SPECIFICATIONS

FREQUENCY RANGE: DC TO 1,000 MHz

VSWR: 1.75:1 MAXIMUM

INSERTION LOSS: .70 dB

ISOLATION: 50 dB MINIMUM

NOMINAL IMPEDANCE: 75 OHMS

POWER HANDLING CAPACITY: 5 WATTS CW, COMMON TO SWITCHED PORTS
(SWITCHED PORTS TERMINATED),
1/2 WATT SWITCHED PORTS TO COMMON

SWITCHING TIME: 15 MILLISECONDS

OPERATING VOLTAGE (ACTUATED TO "B" POSITION): +12 VDC AT 45mA MAXIMUM

OPERATING TEMPERATURE RANGE: - 20°C TO + 60°C

ACTIVE PORT	CONNECTED GROUND	DC POWER
A	YES	OFF
B	YES	ON



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE7101

DES. "75 OHM BNC" FEMALE A/B COAXIAL
SWITCH, FREQUENCY RANGE: DC TO 1,000
MHz

REV. C

FSCM NO. 53919

CAD FILE 100512

SCALE N/A

SIZE A 2233

NOTES:

- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
- DIMENSIONS ARE IN INCHES (mm).