# **Ultra High Performance BGA Cooling Solutions** w/ Thermal Tape Attachment





ATS Part#: Description:

#### ATS-52210B-C1-R0

maxiFLOW<sup>™</sup> Heat Sink, T412, BLUE-ANODIZED

Heat Sink Type: maxiFLOW Heat Sink Attachment: Equivalent Part Number: ATS-52210B-C2-R0

THERMAL TAPE

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes pre-assembled with high performance thermal interface material ٠

### **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 11.86 °C/W          | 9.52 °C/W           | 8.20 °C/W           | 7.33 °C/W           | 6.69 °C/W           | 6.19 °C/W           | 5.79 °C/W           |
|                    | Ducted Flow   | 8.81                | n/a                 | n/a                 | n/a                 | n/a                 | n/a                 | n/a                 |

## **Product Detail**

| Schematic Image                                | Dimension A  | Dimension B           | Dimension C   | Dimension D  | ТІМ                                | Finish                            |
|--|--|-----------------------|---|--|------------------------------------|-----------------------------------|
|  | 21.0 mm  | 21.0 mm               | 7.5 mm  | 34.6 mm  | T412                               | BLUE-ANODIZED                     |
|  | <ul> <li>Dimensior</li> <li>ATS-5221<br/>(Saint Gol</li> <li>Thermal p<br/>application</li> <li>ATS reserve<br/>performant</li> <li>ATS certification</li> </ul> | ves the right to upda | eight from the botton<br>act heat sink assemb<br>provided for referen<br>ate or change its pro-<br>k assembly is RoHS | oly with an equivalen<br>nce only. Actual perf<br>ducts without notice<br>-6 and REACH com | t thermal<br>formance<br>to improv | interface material<br>may vary by |
| *Image above is for illustration purpose only. |  |                       |   |  |                                    |                                   |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA