



Copper Compression Connectors

- For use with copper conductor: AWG stranded, flexible cable, welding cable and portable cord
- Specially designed for industrial and building applications
- Made of high conductivity seamless copper tubing
- Tin-plated for corrosion resistance
- Specially chamfered barrel for ease of installation
- Colour-coded for matching die identification
- Can be used for high voltage application up to 35 kV provided proper high voltage insulation techniques are used
- U. L. Listed for AWG conductor when installed with Blackburn, Burndy, T&B or Anderson tools
- Comply with Subpart 111.60-17 of Federal Register's Coast Guard Electrical Engineering Rules and Regulations

Short Barrel Connectors

- Short barrel connectors designed for regular duty applications
- Ideal for confined areas

Type CSP — Copper Splices, Short Barrel

Cat. No.	Conductor Size (CU)	Length L (in.)	Die Colour Code
CSP8	8 str.	1	Red
CSP6	6 str.	1	Blue
CSP4	4 str.	1	Grey
CSP2	3-2 str.	1¼	Brown
CSP1	1 str.	1½	Green
CSP10	1/0 str.	1¾	Pink
CSP20	2/0 str.	1¾	Black
CSP30	3/0 str.	1¾	Orange
CSP40	4/0 str.	1¾	Purple
CSP250	250 KCMIL	2¼	Yellow
CSP300	300 KCMIL	2½	White
CSP350	350 KCMIL	2¼	Red
CSP400	400 KCMIL	2¼	Blue
CSP500	500 KCMIL	2¾	Brown
CSP600	600 KCMIL	3	Green
CSP750	750 KCMIL	3	Black
CSP1000	1000 KCMIL	3¾	—

