



Thyristor/Diode Modules


VRRM / VDRM 800 to 1600V
ITAV 40Amp

Applications

- Power Converters
- Lighting Control
- DC Motor Control and Drives
- Heat and temperature control

Features

- International standard package
- High Surge Capability
- Glass passivated chip
- Simple Mounting
- Heat transfer through aluminum oxide DCB ceramic isolated metal baseplate



Module Type

TYPE	VRRM	VRSM
MSTC40-08	800V	900V
MSTC40-12	1200V	1300V
MSTC40-16	1600V	1700V

Maximum Ratings

Symbol	Conditions	Values	Units
I_{TAV}	Sine 180°; $T_c=85^\circ\text{C}$	40	A
I_{TSM}	$T_{VJ}=45^\circ\text{C}$ t=10ms, sine	1000	A
	$T_{VJ}=125^\circ\text{C}$ t=10ms, sine	850	
i^2t	$T_{VJ}=45^\circ\text{C}$ t=10ms, sine	5000	A ² s
	$T_{VJ}=125^\circ\text{C}$ t=10ms, sine	3600	
Visol	a.c.50HZ;r.m.s.;1min	3000	V
T_{vj}		-40 to 125	°C
T_{stg}		-40 to 125	°C
Mt	To terminals(M5)	$3 \pm 15\%$	Nm
Ms	To heatsink(M6)	$5 \pm 15\%$	Nm
di/dt	$T_{VJ}=T_{VJM}$, $2/3V_{DRM}$, $I_G=500\text{mA}$ $Tr<0.5\mu\text{s}$, $tp>6\mu\text{s}$	150	A/ μs
dv/dt	$T_J=T_{VJM}$, $2/3V_{DRM}$ linear voltage rise	1000	V/ μs
a	Maximum allowable acceleration	50	m/s ²
Weight	Module(Approximately)	100	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	Cont.;per thyristor / per module	0.65/0.33	°C/W
Rth(c-s)	per thyristor / per module	0.2/0.1	°C/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
V_{TM}	$T=25^{\circ}C$ $I_{TM}=120A$			1.95	V
I_{RRM}/I_{DRM}	$T_{VJ}=T_{VJM}, V_R=V_{RRM}, V_D=V_{DRM}$			15	mA
V_{TO}	For power-loss calculations only ($T_{VJ}=125^{\circ}C$)			1.0	V
r_T	$T_{VJ}=T_{VJM}$			4.5	m Ω
V_{GT}	$T_{VJ}=25^{\circ}C, V_D=6V$			2.5	V
I_{GT}	$T_{VJ}=25^{\circ}C, V_D=6V$			150	mA
V_{GD}	$T_{VJ}=125^{\circ}C, V_D=2/3V_{DRM}$			0.25	V
I_{GD}	$T_{VJ}=125^{\circ}C, V_D=2/3V_{DRM}$			6	mA
I_L	$T_{VJ}=25^{\circ}C, R_G=33\Omega$		300	600	mA
I_H	$T_{VJ}=25^{\circ}C, V_D=6V$		150	260	mA
tgd	$T_{VJ}=25^{\circ}C, I_G=1A, di_G/dt=1A/us$		1		us
tq	$T_{VJ}=T_{VJM}$		80		us




Fig6. Gate trigger Characteristics

Package Outline Information

