

# XUAN 1919 烜

## 36V/25W series



### Introduction

Everlight's COB Series is an aluminum substrate based LED achieving high efficiency while maintaining high CRI at Energy Star / ANSI color temperature ranges.

### Features

- ◆ High Power COB & High CRI LED
- ◆ Multi-Chip Solution
- ◆ Dimension: 19 mm x 19 mm x 1.6 mm
- ◆ Main Parameters: Luminous Flux, Forward Voltage, Chromaticity and Color Rendering Index
- ◆ RoHS compliant
- ◆ Energy Star / ANSI Compliant Binning Structure
- ◆ Typical Viewing Angle: 115°

### Applications

- ◆ Replacement Bulb
- ◆ Indoor General Lighting
- ◆ Recessed Can Lighting

## Table of Contents

|   |    |
|---|----|
| Product Nomenclature .....                          | 3  |
| Absolute Maximum Ratings .....                      | 4  |
| PN of the XUAN1919 36V/25W series:White LEDs .....  | 5  |
| Product Binning:Luminous Flux Bins .....            | 6  |
| Prodcut Binning:Warm White Bin Structure .....      | 7  |
| Product Binning:Warm White Bin Coordinates .....    | 9  |
| Prodcut Binning:Neutral White Bin Structure .....   | 9  |
| Product Binning:Neutral White Bin Coordinates ..... | 8  |
| Prodcut Binning:Cool White Bin Structure .....      | 10 |
| Product Binning:Cool White Bin Coordinates .....    | 10 |
| Product Binning:Forward Voltage Bins .....          | 12 |
| Mechanical Dimension .....                          | 13 |
| Pad Configuration .....                             | 14 |
| Typical Electro-Optical Characteristic Curve .....  | 15 |
| Product Labeling .....                              | 20 |
| Carrier Tray Specification .....                    | 20 |
| Precautions of Use .....                            | 23 |
| Revision History .....                              | 24 |

## Product Nomenclature

The product name is designated as below:

# XUAN1919-CDEFGHJ-KLMNP-QRST

Family name  
XUAN1919

Designation:

CD = lighting color and wavelength<sup>[1]</sup>

EF = color bin or CCT bin

G = internal code

HJ = min. luminous flux (lm) or radiation power (mW) performance

KL = forward voltage bin<sup>[2]</sup>

M = internal code

NP = power consumption<sup>[3]</sup>

Q= internal code

R= Dam Diameter<sup>[4]</sup>

S= internal code

T=Type of Package<sup>[5]</sup>

### Notes

1. Table of lighting color and wavelength

| Symbol | Color         | CCT range  | Color Rendering Index |
|--------|---------------|------------|-----------------------|
| GT     | Cool-White    | 4745~7050K | >65                   |
| KT     | Cool-White    | 4745~7050K | >80                   |
| LM     | Warm-White    | 2580~3710K | >70                   |
|        | Neutral-White | 3710~4745K |                       |
| KM     | Warm White    | 2580~3710K | >80                   |
|        | Neutral-White | 3710~4745K |                       |

2. Table of forward voltage bin

| Symbol | Description       |
|--------|-------------------|
| 36     | 36V Input Voltage |

3. Power consumption:

| Symbol | Description |
|--------|-------------|
| 25     | 25W         |

4. Dam Diameter:


| Symbol | Description |
|--------|-------------|
| E      | 14.0-14.9mm |

5. Table of packaging types:

| Symbol | Description |
|--------|-------------|
| T      | Tray        |

## Absolute Maximum Ratings

| Parameter                                       | Symbol    | Ratings   | Unit |
|---|-----------|-----------|------|
| Max. DC Forward Current (mA) <sub>[4],[5]</sub> | $I_F$     | 1440      | mA   |
| Max. Pulse Forward Current (mA)                 | $I_P$     | 2160      | mA   |
| Power Dissipation                               | $P_d$     | 57        | W    |
| Thermal Resistance                              | $R_{th}$  | 0.46      | °C/W |
| Max. Junction Temperature                       | $T_J$     | 120       | °C   |
| Operating Temperature <sub>[4],[5]</sub>        | $T_{Opr}$ | -40 ~ +85 | °C   |
| Storage Temperature                             | $T_{Stg}$ | -40 ~ +85 | °C   |



**Notes:**

1. For optimal performance, Everlight recommends 720mA operation.
2.  $t_p \leq 100ms$ , Duty cycle = 25%
3. The XUAN1919 36V/25W series LEDs are not designed for reverse bias use.
4. Power dissipation and forward current are the value when the module temperature is set lower than the rating by using an adequate heat sink.
5.  $T_b = 25\text{ }^\circ\text{C}$

**PN of the XUAN1919 Series : White LEDs**



| Color              | Order Code of XUAN1919      | Minimum Luminous Flux (lm) | Typical Luminous Flux (lm) | CCT (K)     | Forward Voltage (V) | Forward Current (mA) | CRI (min.) |
|--------------------|-----------------------------|----------------------------|----------------------------|-------------|---------------------|----------------------|------------|
| Warm White 2700    | XUAN1919-KM277S3-36C25-3E0T | 2600                       | 2910                       | 27K-1~27K-4 | 33.0~41.0           | 720                  | 80         |
| Warm White 3000    | XUAN1919-KM307S4-36C25-3E0T | 2800                       | 3050                       | 30K-1~30K-4 | 33.0~41.0           | 720                  | 80         |
| Warm White 3500    | XUAN1919-KM357S4-36C25-3E0T | 2800                       | 3135                       | 35K-1~35K-4 | 33.0~41.0           | 720                  | 80         |
| Neutral White 4000 | XUAN1919-KM407S4-36C25-3E0T | 2800                       | 3220                       | 40K-1~40K-4 | 33.0~41.0           | 720                  | 80         |
| Neutral White 4500 | XUAN1919-KM457S4-36C25-3E0T | 2800                       | 3230                       | 45K-1~45K-4 | 33.0~41.0           | 720                  | 80         |
| Cool White 5000    | XUAN1919-KT507S5-36C25-3E0T | 3000                       | 3335                       | 50K-1~50K-4 | 33.0~41.0           | 720                  | 80         |
| Cool White 5700    | XUAN1919-KT577S5-36C25-3E0T | 3000                       | 3360                       | 57K-1~57K-4 | 33.0~41.0           | 720                  | 80         |
| Cool White 6500    | XUAN1919-KT657S5-36C25-3E0T | 3000                       | 3360                       | 65K-1~65K-4 | 33.0~41.0           | 720                  | 80         |

**Notes:**

1. CRI measurement tolerance:  $\pm 2$ .
2. Luminous flux measurement tolerance:  $\pm 10\%$ .
3. The data of luminous flux measured at thermal pad=25°C
4. Typical luminous flux or light output performance is operated within the condition guided by this datasheet.


## Product Binning

### Luminous Flux Bins

| Group | Bin | Minimum Photometric Flux (lm) | Maximum Photometric Flux (lm) |
|-------|-----|-------------------------------|-------------------------------|
| J     | 1   | 100                           | 110                           |
|       | 2   | 110                           | 120                           |
|       | 3   | 120                           | 130                           |
|       | 4   | 130                           | 140                           |
|       | 5   | 140                           | 150                           |
|       | 6   | 150                           | 160                           |
|       | 7   | 160                           | 180                           |
|       | 8   | 180                           | 200                           |
|       | 9   | 200                           | 225                           |
| K     | 1   | 225                           | 250                           |
|       | 2   | 250                           | 275                           |
|       | 3   | 275                           | 300                           |
|       | 4   | 300                           | 325                           |
|       | 5   | 325                           | 350                           |
|       | 6   | 350                           | 375                           |
|       | 7   | 375                           | 400                           |
|       | 8   | 400                           | 425                           |
|       | 9   | 425                           | 450                           |
| N     | 1   | 450                           | 475                           |
|       | 2   | 475                           | 500                           |
|       | 3   | 500                           | 550                           |
|       | 4   | 550                           | 600                           |
|       | 5   | 600                           | 650                           |
|       | 6   | 650                           | 700                           |
|       | 7   | 700                           | 750                           |
|       | 8   | 750                           | 800                           |
|       | 9   | 800                           | 900                           |
| P     | 1   | 900                           | 1000                          |
|       | 2   | 1000                          | 1100                          |
|       | 3   | 1100                          | 1200                          |
|       | 4   | 1200                          | 1350                          |
|       | 5   | 1350                          | 1500                          |
|       | 6   | 1500                          | 1650                          |
|       | 7   | 1650                          | 1800                          |
|       | 8   | 1800                          | 2000                          |
|       | 9   | 2000                          | 2200                          |

| Group | Bin | Minimum Photometric Flux (lm) | Maximum Photometric Flux (lm) |
|-------|-----|-------------------------------|-------------------------------|
| S     | 1   | 2200                          | 2400                          |
|       | 2   | 2400                          | 2600                          |
|       | 3   | 2600                          | 2800                          |
|       | 4   | 2800                          | 3000                          |
|       | 5   | 3000                          | 3200                          |
|       | 6   | 3200                          | 3400                          |
|       | 7   | 3400                          | 3600                          |
|       | 8   | 3600                          | 3800                          |
|       | 9   | 3800                          | 4000                          |
| M     | 1   | 4000                          | 4200                          |
|       | 2   | 4200                          | 4400                          |
|       | 3   | 4400                          | 4600                          |
|       | 4   | 4600                          | 4800                          |
|       | 5   | 4800                          | 5000                          |
|       | 6   | 5000                          | 5200                          |
|       | 7   | 5200                          | 5400                          |
|       | 8   | 5400                          | 5600                          |
|       | 9   | 5600                          | 5800                          |
| Q     | 1   | 5800                          | 6000                          |
|       | 2   | 6000                          | 6200                          |
|       | 3   | 6200                          | 6400                          |
|       | 4   | 6400                          | 6600                          |
|       | 5   | 6600                          | 6800                          |
|       | 6   | 6800                          | 7000                          |
|       | 7   | 7000                          | 7200                          |
|       | 8   | 7200                          | 7400                          |
|       | 9   | 7400                          | 7600                          |

### Warm-White Bin Structure



### Warm-White Bin Coordinates

#### 2700K

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 27K-1                       | 0.4582 | 0.4099 |
|                             | 0.4687 | 0.4289 |
|                             | 0.4813 | 0.4319 |
|                             | 0.4700 | 0.4126 |
| Reference Range: 2580~2718K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 27K-2                       | 0.4465 | 0.4071 |
|                             | 0.4562 | 0.4260 |
|                             | 0.4687 | 0.4289 |
|                             | 0.4582 | 0.4099 |
| Reference Range: 2718~2869K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 27K-4                       | 0.4483 | 0.3919 |
|                             | 0.4582 | 0.4099 |
|                             | 0.4700 | 0.4126 |
|                             | 0.4593 | 0.3944 |
| Reference Range: 2580~2718K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 27K-3                       | 0.4373 | 0.3893 |
|                             | 0.4465 | 0.4071 |
|                             | 0.4582 | 0.4099 |
|                             | 0.4483 | 0.3919 |
| Reference Range: 2718~2869K |        |        |

#### 3000K


| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 30K-1                       | 0.4342 | 0.4028 |
|                             | 0.4430 | 0.4212 |
|                             | 0.4562 | 0.4260 |
|                             | 0.4465 | 0.4071 |
| Reference Range: 2870~3000K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 30K-2                       | 0.4221 | 0.3984 |
|                             | 0.4299 | 0.4165 |
|                             | 0.4430 | 0.4212 |
|                             | 0.4342 | 0.4028 |
| Reference Range: 3000~3220K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 30K-4                       | 0.4147 | 0.3814 |
|                             | 0.4221 | 0.3984 |
|                             | 0.4342 | 0.4028 |
|                             | 0.4259 | 0.3853 |
| Reference Range: 2870~3000K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 30K-3                       | 0.4259 | 0.3853 |
|                             | 0.4342 | 0.4028 |
|                             | 0.4465 | 0.4071 |
|                             | 0.4373 | 0.3893 |
| Reference Range: 3000~3220K |        |        |

Warm-White Bin Structure



Warm-White Bin Coordinates

3500K

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 35K-1                       | 0.4080 | 0.3916 |
|                             | 0.4146 | 0.4089 |
|                             | 0.4299 | 0.4165 |
|                             | 0.4221 | 0.3984 |
| Reference Range: 3209~3448K |        |        |


| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 35K-2                       | 0.3941 | 0.3848 |
|                             | 0.3996 | 0.4015 |
|                             | 0.4146 | 0.4089 |
|                             | 0.4080 | 0.3916 |
| Reference Range: 3449~3710K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 35K-4                       | 0.3889 | 0.3690 |
|                             | 0.3941 | 0.3848 |
|                             | 0.4080 | 0.3916 |
|                             | 0.4017 | 0.3751 |
| Reference Range: 3209~3448K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 35K-3                       | 0.4017 | 0.3751 |
|                             | 0.4080 | 0.3916 |
|                             | 0.4221 | 0.3984 |
|                             | 0.4147 | 0.3814 |
| Reference Range: 3449~3710K |        |        |



### Neutral-White Bin Structure



### Neutral-White Bin Coordinates

#### 4000K

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 40K-1                       | 0.3825 | 0.3798 |
|                             | 0.3869 | 0.3958 |
|                             | 0.4006 | 0.4044 |
|                             | 0.3950 | 0.3875 |
| Reference Range: 3710~3967K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 40K-2                       | 0.3702 | 0.3722 |
|                             | 0.3736 | 0.3874 |
|                             | 0.3869 | 0.3958 |
|                             | 0.3825 | 0.3798 |
| Reference Range: 3967~4259K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 40K-4                       | 0.3783 | 0.3646 |
|                             | 0.3825 | 0.3798 |
|                             | 0.3950 | 0.3875 |
|                             | 0.3898 | 0.3716 |
| Reference Range: 3710~3967K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 40K-3                       | 0.3670 | 0.3578 |
|                             | 0.3702 | 0.3722 |
|                             | 0.3825 | 0.3798 |
|                             | 0.3783 | 0.3646 |
| Reference Range: 3967~4259K |        |        |

#### 4500K


| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 45K-1                       | 0.3641 | 0.3804 |
|                             | 0.3736 | 0.3874 |
|                             | 0.3702 | 0.3722 |
|                             | 0.3615 | 0.3659 |
| Reference Range: 4259~4490K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 45K-2                       | 0.3548 | 0.3736 |
|                             | 0.3641 | 0.3804 |
|                             | 0.3615 | 0.3659 |
|                             | 0.3530 | 0.3597 |
| Reference Range: 4490~4744K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 45K-4                       | 0.3530 | 0.3597 |
|                             | 0.3615 | 0.3659 |
|                             | 0.3590 | 0.3521 |
|                             | 0.3512 | 0.3465 |
| Reference Range: 4259~4490K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 45K-3                       | 0.3615 | 0.3659 |
|                             | 0.3702 | 0.3722 |
|                             | 0.3670 | 0.3578 |
|                             | 0.3590 | 0.3521 |
| Reference Range: 4490~4744K |        |        |

Cool-White Bin Structure



Cool-White Bin Coordinates

5000K

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 50K-1                       | 0.3463 | 0.3687 |
|                             | 0.3551 | 0.3760 |
|                             | 0.3533 | 0.3620 |
|                             | 0.3451 | 0.3554 |
| Reference Range: 4743~5011K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 50K-2                       | 0.3376 | 0.3616 |
|                             | 0.3463 | 0.3687 |
|                             | 0.3451 | 0.3554 |
|                             | 0.3371 | 0.3490 |
| Reference Range: 5013~5308K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 50K-4                       | 0.3451 | 0.3554 |
|                             | 0.3533 | 0.3620 |
|                             | 0.3515 | 0.3487 |
|                             | 0.3440 | 0.3427 |
| Reference Range: 4743~5011K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 50K-3                       | 0.3371 | 0.3490 |
|                             | 0.3451 | 0.3554 |
|                             | 0.3440 | 0.3427 |
|                             | 0.3366 | 0.3369 |
| Reference Range: 5013~5308K |        |        |

5700K


| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 57K-1                       | 0.3290 | 0.3538 |
|                             | 0.3376 | 0.3616 |
|                             | 0.3371 | 0.3490 |
|                             | 0.3290 | 0.3417 |
| Reference Range: 5308~5643K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 57K-2                       | 0.3207 | 0.3462 |
|                             | 0.3290 | 0.3538 |
|                             | 0.3290 | 0.3417 |
|                             | 0.3215 | 0.3350 |
| Reference Range: 5643~6017K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 57K-4                       | 0.3290 | 0.3417 |
|                             | 0.3371 | 0.3490 |
|                             | 0.3366 | 0.3369 |
|                             | 0.3290 | 0.3300 |
| Reference Range: 5308~5643K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 57K-3                       | 0.3215 | 0.3350 |
|                             | 0.3290 | 0.3417 |
|                             | 0.3290 | 0.3300 |
|                             | 0.3222 | 0.3243 |
| Reference Range: 5643~6017K |        |        |

### Cool-White Bin Structure



### Cool-White Bin Coordinates

#### 6500K

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 65K-1                       | 0.3115 | 0.3391 |
|                             | 0.3205 | 0.3481 |
|                             | 0.3213 | 0.3373 |
|                             | 0.3130 | 0.3290 |
| Reference Range: 6018~6493K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 65K-2                       | 0.3028 | 0.3304 |
|                             | 0.3115 | 0.3391 |
|                             | 0.3130 | 0.3290 |
|                             | 0.3048 | 0.3207 |
| Reference Range: 6487~7042K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 65K-4                       | 0.3130 | 0.3290 |
|                             | 0.3213 | 0.3373 |
|                             | 0.3221 | 0.3261 |
|                             | 0.3144 | 0.3186 |
| Reference Range: 6018~6493K |        |        |

| Bin                         | CIE X  | CIE Y  |
|-----------------------------|--------|--------|
| 65K-3                       | 0.3048 | 0.3207 |
|                             | 0.3130 | 0.3290 |
|                             | 0.3144 | 0.3186 |
|                             | 0.3068 | 0.3113 |
| Reference Range: 6487~7042K |        |        |

#### Notes:

1. Color coordinates measurement allowance :  $\pm 0.01$ .

### Forward Voltage Bins


| Bin | Minimum Forward Voltage (V) | Maximum Forward Voltage (V) |
|-----|-----------------------------|-----------------------------|
| W4  | 33.0                        | 35.0                        |
| W5  | 35.0                        | 37.0                        |
| W6  | 37.0                        | 39.0                        |
| W7  | 39.0                        | 41.0                        |

**Notes:**

1. Forward voltage measurement tolerance:  $\pm 2\%$ .
2. Forward voltage bins are defined at  $I_f=720\text{mA}$  operation.
3. Other Forward Voltage bins for White LEDs available upon request. Please contact your local Everlight sales office.




## Pad Configuration




| PAD | FUNCTION |
|-----|----------|
| 1   | ANODE    |
| 2   | CATHODE  |

## Typical Electro-Optical Characteristic Curve


Relative Spectral Distribution  
@ Substrate Temperature = 25°C




Relative Luminous Flux vs. Substrate Temperature  
@Forward Current = 720mA



**Forward Voltage vs. Forward Current**  
@ Substrate Temperature = 25°C




**Luminous Flux vs. Forward Current**  
@ Substrate Temperature = 25°C







**Correlated Color Temperature vs. Forward Current**  
**@ Substrate Temperature = 25°C**




**Correlated Color Temperature vs. Substrate Temperature**  
**@ Forward Current = 720mA**




**Forward Voltage vs. Substrate Temperature**  
**@ Forward Current = 720mA**



**Forward Current Derating Curve**  
**@ Junction Temperature <120°C**



### Typical Diagram Characteristics of Radiation Patterns



**Notes:**

1.  $2\theta_{1/2}$  is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
2. Viewing angle tolerance is  $\pm 5^\circ$

## Product Labeling

### Label Explanation

CPN: Customer Specification (when required)

P/N : Everlight Production Number

QTY: Packing Quantity

CAT: Luminous Flux (Brightness) Bin

HUE: Color Bin

REF: Forward Voltage Bin


LOT No: Lot Number

MADE IN TAIWAN: Production Place



## Carrier Tray Specification

Loaded Quantity: 63 PCS Per Tray



### Notes:

1. Dimensions are in millimeters
2. Tolerances unless mentioned are  $\pm 0.1\text{mm}$


### LED Direction

- The **Recycle mark** on the LEDs will be toward the **Anode mark** on the carrier tray.

### Moisture Resistant Packaging



### Outside Carton



### Packaging Quantity

- 63 PCS Per Tray
- 20 Trays Per Outside Carton



## Precautions of Use

### Over-Current-Proof

- Though the XUAN1919 has a conducted ESD protection mechanism, customers must not use the device in reverse and should apply resistors for extra protection. Otherwise slight voltage shift may cause significant current changes and burn out failure may happen.

### Storage Conditions

- Before the package is opened: The LEDs should be stored at 30°C or less and 50%RH or less after being shipped from Everlight and the storage life limit is 6 months. If the LEDs are stored for 6 months or more, they should be stored in a sealed container with a nitrogen atmosphere and moisture absorbent material.
- After opening the package: The LED should be stored under 30°C or less and 30%RH or less. The LED should be used within 168hrs (7days) after opening the package. If unused LEDs remain, it should be stored in moisture proof packages.
- Do not stack assemblies.




## Handling

- Do not put mechanical stress on the LED.
- Never touch the optical surface with finger or sharp object. The LED surface could be soiled or damaged, which could affect the optical performance of the LED.
- In low-humidity work environment, please keep handling the LEDs with appropriate ESD grounding.
- It is recommended to handle the LED with powder-less latex gloves.

## Manual Handling

- When handling the product, do not apply direct pressure on the optical surface.
- Do not touch the resin with tweezers to avoid scratching or other damage.



## Thermal Management

- Sufficient thermal management must be implemented. Substrate of the positive in temperature must be kept under 85°C at the driving current of 720mA. Otherwise, the junction temperature of die may exceed the limit at high current driving conditions and the LEDs' lifetime may be decrease dramatically.

## Revision History

Current version: **2013/12/13**

Previous version: **N/A**

Device No.DHE-0002306

Rev. Ver. 3

| Page | Subjects (major change in previous version) | Date of change |
|------|---|----------------|
| 5    | Add 6500K Bin                               | 2014/04/01     |
|      |   |                |
|      |   |                |
|      |   |                |