



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: x.x=± 0.4mm
x.xx=± 0.25mm
3. RATING: DC 30V, 0.3A
4. OPERATING FORCE: 200 ± 100gf
5. TRAVEL: 3.3mm FULL TRAVEL 2.5mm TO LOCK
6. LIFE CYCLES: 10,000 CYCLES
7. OPERATING TEMPERATURE: -20°C TO 70°C
8. CONTACT RESISTANCE: 20 milli-Ohms MAX.
9. INSULATION RESISTANCE: 100 Mega-OHMS MIN@ 500VDC.
- ▲10. LED COLOR: RED / GREEN
11. ▲ DENOTES CRITICAL PARAMETER.
12. 2002/95/EC (RoHS) COMPLIANT.

LED SPECS	UNITS	RED	GREEN
FORWARD CURRENT	mA	20	20
FORWARD VOLTAGE @20mA	V	1.7 Typ-2.6 Max	1.7 Typ - 2.6 Max
LUMINOUS INTENSITY @ 10mA	MCD	1.6-2.6	4.7 - 7.8

REV	PCR NO	DESCRIPTION	DATE	BY
D	19872	EDIT LED CIRCUIT	4/25/11	BGL
C	19529	DRAWING UPDATE / CLEAN UP	12/14/10	BGL
B	19504	CORRECT LED CALL-OUT	12/07/10	BMA
A	18981	Release For Production	4/1/10	BLR

TITLE WBL2UEERGQ				
SCALE	DATE	DR	DWG	REV
2	4/1/2010	BLR	B400005	D

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED