



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X ± 0.4  
X.XX ± 0.30
3. TERM. NOS. FOR REF. ONLY
4. RATING: 50mA, @12V DC
5. TRAVEL: 0.25 +0.20 /-0.10 mm
6. CONTACT RESISTANCE: 50m ohms max initial.  
(CMOS & TTL COMPATIBLE)
7. ELECTRICAL LIFE: 1,000,000 CYCLES
8. INSULATION RESISTANCE: 100M ohms min.
9. DIELECTRIC STRENGTH: 250VAC, 1 MIN.
10. OPERATING TEMP.: -20°C to 70°C
11. ▲ DENOTES CRITICAL PARAMETER
12. CONTACTS: SILVER
13. OPERATING FORCE: 65 ± 20 GRAMS
14. PACKAGING: 1000 PCS PER POLYBAG
15. 2002/95/EC (ROHS) COMPLIANT



|     |        |                           |          |     |
|-----|--------|---------------------------|----------|-----|
| B   | 18742  | LEG TOLERANCE WAS +/- 0.1 | 1/4/2010 | BLR |
| A   | 16277  | RELEASED FOR PRODUCTION   | 8/8/06   | BO  |
| REV | PCR NO | DESCRIPTION               | DATE     | BY  |

|                    |          |     |         |     |
|--------------------|----------|-----|---------|-----|
| TITLE LL1105WF065Q |          |     |         |     |
| SCALE              | DATE     | DR  | DWG     | REV |
| 4:1                | 1/4/2010 | BLR | P090006 | B   |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED