


Features

- 175 °C T_J operation
- Low forward voltage drop
- High frequency operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Lead (Pb)-free plating
- Designed and qualified for industrial level



DO-201AD		
Dim	Min	Max
A	25.40	—
B	7.20	9.50
C	1.20	1.30
D	4.80	5.30
All Dimensions in mm		

Mechanical Data

- Case: Molded Plastic

Maximum Ratings and Electrical Characteristics @ T_A = 25°C unless otherwise specified

SYMBOL	CHARACTERISTICS	VALUES				UNITS
I _{F(AV)}	Rectangular waveform	8				A
V _{RRM}	Range	30 to 45				V
I _{FSM}	t _p = 5 μs sine	2400				A
V _F	8 Apk, T _J = 125 °C	0.44				V
T _J	Range	- 55 to 175				°C
PARAMETER	SYMBOL	80SQ030	80SQ035	80SQ040	80SQ045	UNITS
Maximum DC reverse voltage	V _R	30	35	40	45	V
Maximum working peak reverse voltage	V _{RWM}					




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance Z_{thJL} Characteristics




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current




Fig. 8 - Unclamped Inductive Test Circuit