



- NOTES:
- FOR USE WITH BOEING BMS13-65 OH & ADAMS RUSSELL FC28Z CABLES.
 - FOR CABLING INSTRUCTIONS SEE 3-546-2.
 - FOR CRIMPING USE DIE KTH-2212.
 - INTERFACE PER MIL-STD-348, FIG. 304-2.
 - FOR USE WITH .22 MAX. PANEL.
 - CENTER CONTACT (1-534-95MA9) SUPPLIED UNASSEMBLED.
 - MARK PACKAGE: KINGS 1201-13-9 (DATE CODE)
 - MATERIALS:
INSULATOR: TEFLON, ASTM-D1710
K-GRIP SLEEVE: COM. BRONZE TUBE, ASTM B135
CENTER CONTACT: BER. COP., ASTM-B196
ALL OTHER PARTS: BRASS, ASTM-B16

- FINISHES:
CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM-B488 OVER .000050 MIN. NICKEL
PER AMS-QQ-N-290 (RoHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER
PER ASTM B734 (RoHS)
- ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
VOLTAGE RATING: 1000 VRMS
FREQUENCY RANGE: DC TO 11 GHz
INSERTION LOSS: DC TO 2.7 GHz, 0.025 dB MAX
2.7 TO 5.0 GHz, 0.035 dB MAX
- WEIGHT: 40.6 GRAMS

1201-13-9

REVISIONS		
ISSUE	CHANGES	
0	ER JCA	33862 04/21/92
1	CN MJB	34086 E 08/19/92
2	ER RMS	8354 05/29/08
D	REVISED PER DMF304 & ER34205 KPL 08/05/11	

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE	4:1	
APPROX SURFACE AREA		
WAS:	E-17401	
CAGE CODE:	91836	
REF:	BOEING	
<h1>JACK, PANEL, N</h1>		
DRAWN	JCA	DATE 04/21/92
DESIGN	JT	DATE 04/22/92
APPR.		DATE


 Winchester Electronics Corporation
 62 Barnes Industrial Road North
 Wallingford, Connecticut 06492

1201-13-9