



Section A-A

NOTES:

MATERIAL

- 1. Insulator Material: PBT+30%GF(UL94V-0)
- 2. Contact Material : Brass
- 3. Contact Plating :
AWP xx-8241-T : Gold flash over Ni
AWP xx-8541-T : Tin over Ni

ELECTRICAL

- 1. Current Rating : 3AMP
- 2. Voltage Rating : 500V AC/DC
- 3. Withstand Voltage : 1000V AC/DC
- 4. Contact Resistance : 20mΩ max
- 5. Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

- 1. Operation Temperature: -40°C to +105°C
- 2. Packing: Tray

RoHS compliant

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	25.01.2006	Alex	
X.X	±0.40					Approved	21.12.2009	Hellwig	ASSMANN WSW-No. AWP xx-8x41-T
X.XX	±0.25								Drawing-No.
X.XXX	±0.15								ASS 2261 CO
Angle	±3°	②	Update	21.12.2009	Dean				rev02
		①	Drawn	25.01.2006	Alex			Replace	Sheet
		Id.	Modification	Date	Name				

Customer-No.
ASSMANN WSW-No.
AWP xx-8x41-T
Drawing-No.
ASS 2261 CO rev02
Replace Sheet

