


RECOMMENDED PCB LAYOUT



SPDT CIRCUIT CONTACT CONFIGURATION

SWITCH FUNCTION			
PDS. 1	PDS. 2	PDS. 3	
DN	NONE	DN	
2-3	OPEN	2-1	

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. RATING: 0.4(VA) Max. @20V (AC or DC)
5. FIXED TERM. & MOVING CONTACT: Cu Alloy w/Gold plate over Ni plate.
6. ELECTRIC LIFE: 50,000 make-and-break cycles at full load.
7. INSULATION RESISTANCE: 1,000 Mega-ohm min.
8. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
9. OPERATING TEMP.: -30C to 85C

B	21002	13.54 WAS 13.39	2/4/13	EBP
A	11468	RELEASED FOR PRODUCTION	5/15/01	CB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		2004 WMSPI11A1M2RE		
SCALE	DATE	DR	DWG	REV
2:1	5/15/01	CB	T201111	B

