

ADAM-2051Z

ADAM-2051PZ

Wireless Sensor Network 8-ch Digital Input Node

Wireless Sensor Network 8-ch Digital Input Node with Power Amplifier



ADAM-2051Z



Features

- IEEE 802.15.4 Wireless Standard
- Supports Star/Tree/Mesh Network Topologies
- Modbus Communication Protocol
- Low Power Consumption
- LED Indicators
- Event Triggering

Specifications

Digital Input

- **Channels** 8
 - **Input Resistance** 10 K Ω
 - **Input Level**
 - Dry contact: Logic level 0: Close to GND
Logic level 1: Open
 - Wet contact: Logic level 0: 0-0.8 V max
Logic level 1: 2.0 ~ 5.0 V
- (Note: The Digital Input Level 0 and 1 status can be inverted)

Ordering Information

- **ADAM-2051Z*** Wireless 8-ch Digital Input Node



ADAM-2051PZ



Features

- IEEE 802.15.4 Wireless Standard
- Supports Star/Tree/Mesh Network Topologies
- Modbus Communication Protocol
- LED Indicators
- Event Triggering

Specifications

Digital Input

- **Channels** 8
 - **Input Resistance** 10 K Ω
 - **Input Level**
 - Dry contact: Logic level 0: Close to GND
Logic level 1: Open
 - Wet contact: Logic level 0: 0-0.8 V max
Logic level 1: 2.0 ~ 5.0 V
- (Note: The Digital Input Level 0 and 1 status can be inverted)

Ordering Information

- **ADAM-2051PZ*** Wireless 8-ch Digital Input Node with Power Amplifier

Common Specifications

Wireless Communication

- **IEEE Standard** IEEE 802.15.4
- **Modulation Type** DSSS (OQPSK)
- **Frequency Band** ISM 2.4 GHz
(2.4 GHz ~ 2.4835 GHz)
- **Channels** 11 - 26
- **RF Data Rate** 250 Kbps
- **Transmit Power Typ.** 3 \pm 1 dBm (ADAM-2051Z)
19 \pm 1 dBm (ADAM-2051PZ)
- **Receiver Sensitivity** -97 dBm
- **Topologies** Star / Tree / Mesh
- **Outdoor Range** 110 m with line of sight (ADAM-2051Z)
1000 m with line of sight (ADAM-2051PZ)
- **Function** End Device

General

- **Connectors** 1 x plug-in terminal block (#14 ~ 22 AWG)
- **Power Input** Unregulated 10 ~ 30 V_{DC}
- **Battery Input** 2 x AA Alkaline
- **Power Consumption** 0.3 W @ 24 V_{DC}
(ADAM-2051Z/PZ) Battery AA * 2
380 uW @ 3 V_{DC} (1 minute Tx Interval)
220 uW @ 3 V_{DC} (2 minute Tx Interval)
130 uW @ 3 V_{DC} (5 minute Tx Interval)

Environment

- **Operating Temperature**
 - External Power -20°C ~ 70°C (-4°F ~ 157.9°F)
 - Battery Power 0°C ~ 50°C (32°F ~ 122°F)
- **Storage Temperature** -20°C ~ 70°C (-4°F ~ 157.9°F)
- **Operating Humidity** 20~95% RH
- **Storage Humidity** 0~95% RH

*If want to operate in a wider temperature (-40°C~ 85°C (-4°F ~ 157.9°F)), contact our sales team.