

SmartRack 12,000 BTU 230V Portable Air Conditioning Unit - Small Server Rooms & Network Closets

MODEL NUMBER: SRXCOOL12K



Description

With 12,000BTU of cooling power, the 230V, 50 Hz SRXCOOL12K is ideal for use in data centers, server and wiring closets, IT environments, home and small business offices, conference rooms, warehouses, entertainment centers or other venues with heat-sensitive equipment, particularly in areas that facility air conditioning can't reach. The SRXCOOL12K not only adjusts ambient room temperatures, but can also dehumidify and filter the air, providing better air quality for enhanced equipment performance with minimal noise and power consumption.

The SRXCOOL12K has a built-in evaporator that expels the condensed water through the exhaust duct, so there is no need for a drain tube, drain pan or water collection tank. Both a standard louvered vent (for general room cooling) and a directional ducted cooling vent (to direct cold air where most needed) are provided. A directional exhaust duct safely removes hot air from the room. SRXCOOL12K comes equipped with an auto-restart feature that retains all system settings and returns the unit back to its last operational state after AC power is restored. A built-in timer enables the unit to be programmed for unattended start-up and shutdown. Controls and displays are conveniently mounted on the top panel. With the optional added accessory of the SRCOOLNET, this communication port allows users to monitor temperatures, receive alerts, review logs and control settings from any location. Designed for quick and simple installation, the SRXCOOL12K rolls into place on built-in casters and plugs into a standard Schuko CEE7 outlet. An included window/drop ceiling kit provides multiple installation options.

The SRXCOOL12K uses environmentally friendly R410a refrigerant, which complies with EPA standards for 2010 and beyond, and is accepted worldwide.

Features

- 12,000 BTU of cooling power can cool a 500 square foot room

Highlights

- Compact, portable, self-contained design reduces maintenance—no water collection tank or drain required
- Rolls into place on built-in casters; does not require an external condenser, refrigerant piping or hiring outside contractors
- Cool a 500 square foot room with 12,000 BTU of cooling power
- Offers both hot-spot and general room cooling with two exchangeable vent styles
- Filters and dehumidifies air to protect equipment
- Auto-restart feature retains all system settings and returns unit back to its last operational state after AC power is restored
- Allows you to monitor temperatures, receive alerts, review logs and control settings from any location (requires SRCOOLNET accessory)

Applications

Supplemental cooling for confined server rooms where the facility HVAC is inadequate or unavailable.

Package Includes

- SRXCOOL12K cooling unit
- Louvered front vent
- Directional front vent
- Cold Air directional delivery tube
- Hot exhaust air removal tube
- Dropped ceiling or window heat ventilation kit
- Warranty information
- Instruction manual



- Uses environmentally friendly R410a refrigerant
- No water collection tank required. A built-in evaporator expels condensate into the exhaust air stream meaning no drain tube, drain pan or water collection tank that needs to be emptied every few hours
- Cold air output can be precisely directed through a 71" flexible tube to the 'hot spot' for better, faster cooling. (Standard louvered insert is also included for general room cooling)
- Auto-restart feature retains all system settings and returns the unit back to its last operational state after AC power is restored
- Communication port allows users to monitor temperatures, receive alerts, review logs and control settings from any location (requires SRCOOLNET accessory)
- Compact, portable, self-contained design; ideal for IT, industrial, commercial and similar applications
- Quick and easy installation. Plugs into a standard Schuko CEE7 outlet
- Window/drop ceiling installation kit is included for extracting heat
- Offers 3 different cycles (cool, dehumidify and fan)
- Cools in confined spaces where facility air conditioning can't reach
- Dehumidifies and filters air to promote more efficient equipment performance
- Built-in timer for automatic unattended start-up and shutdown
- System lock function disables all other buttons to prevent accidental input
- Quiet operation with minimal power consumption
- Convenient top-mounted controls and displays
- 220-240V AC input, 50 Hz frequency compatibility

Specifications

INPUT	
Nominal Input Voltage(s) Supported	220V AC; 230V AC; 240V AC
Input Connection Type	Schuko CEE7
Input Cord Length (ft.)	6
Input Cord Length (m)	1.8
USER INTERFACE, ALERTS & CONTROLS	
Front Panel LEDs	Touch sensitive control panel with multiple LEDs and numerical temperature readout
PHYSICAL	
Shipping Dimensions (hwd / in.)	33.46 x 15.16 x 29.13
Shipping Dimensions (hwd / cm)	85 x 38.5 x 74
Shipping Weight (lbs.)	77.25
Shipping Weight (kg)	34.76
Unit Dimensions (hwd / in.)	30.63 x 11.81 x 19.88
Unit Dimensions (hwd / cm)	77.8 x 30 x 50.5
Unit Weight (lbs.)	73.9
Unit Weight (kg)	33.5



Material of Construction	ABS
Color	Black
Form Factors Supported	Tower
ENVIRONMENTAL	
Cooling Capacity	12,000 BTU / 3.5 kW
SPECIAL FEATURES	
Dehumidifier	2.5lbs / hour
Compressor Type	Rotary
Refrigerant	R410a (Environmentally friendly, Non ozone depleting)
Refrigerant Amount	22 oz.
Air Flow	Evaporator = 329 CFM / Condenser = 311 CFM
Amp Draw Nominal	7-10A
Sound Level (Noise)	57dB
Air Supply Tube Length	71 inches
Air Exhaust Tube Length	118 inches
Air Exhaust Tube Diameter	5.16 inches
CERTIFICATIONS	
Certifications	Tested to CE; RoHS
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>