



# VL Plus Colors

## Everyday standard face lit solutions

VL Plus LED lighting system is based on proven SloanLED channel letter module design and performance. VL Plus offers a variety of solutions and a wide selection of colors.

- Two red sizes: Long and Short
- Shorts are available in 5 bright colors
- Constant Current Technology (CCT)



### Specifications

<b>Part number</b>	Long	Red	701269-RVLL-MB
	Short	Red	701269-RVLS-MB
		Orange	701269-ORSA1-MB
		Yellow	701269-YLSA1-MB
		Green	701269-GRSA1-MB
		Blue	701269-BLSA1-MB
<b>Dimensions L × W × H</b>	Long	3.45 in × 0.49 in × 0.37 in	
	Short	2.35 in × 0.49 in × 0.37 in	
<b>Viewing angle</b>	120°		
<b>LEDs per module</b>	3		
<b>Modules per foot</b>	Long	2	
	Short	2.5	
<b>Maximum coverage per row</b>	<b>Can depth</b>	<b>Coverage</b>	
	5 in	5 in	
<b>Operating temperature</b>	-40° C to +70° C		
<b>Protection class</b>	IP66		
<b>Power per module</b>	Long	Red	0.36 W
	Short	Red, Orange, Yellow	0.29 W
		Green, Blue	0.36 W
<b>Efficacy</b>	Red	31 lm/W	
	Orange	45 lm/W	
	Yellow	28 lm/W	
	Green	86 lm/W	
	Blue	25 lm/W	
<b>Power capacity</b>	Per SloanLED 60 W 12 VDC power supply:		
	Long	Red	150 modules
	Short	Red, Orange, Yellow	187 modules
		Green, Blue	150 modules
<b>Fastening</b>	Peel-n-stick and mechanical		
<b>Packaging</b>	5 trays per carton		
	Long	25 ft (50 modules) per tray	
	Short	30 ft (75 modules) per tray	



# VL Plus Colors

Everyday standard face lit solutions

## Specifications *cont'd*

Size	Color	Part number	Nominal wavelength	Lumens per module (nominal)
Long	Red	701269-RVLL-MB	625 nm	11
Short	Red	701269-RVLS-MB	625 nm	9
	Orange	701269-ORSA1-MB	610 nm	13
	Yellow	701269-YLSA1-MB	590 nm	8
	Green	701269-GRSA1-MB	528 nm	31
	Blue	701269-BLSA1-MB	470 nm	9

