


# LVC-5000-A2

Fanless Mobile DVR with Intel Celeron 1047UE & 16CH Analogue Video for Transport Surveillance Solution



## Features

### Multiple LAN ports to support Transport Surveillance

This mobile NVR with 4 GbE LAN ports is suitable for IP Video Surveillance and real-time recording applications.

### Designed for MIL-STD-810G with Extreme Vibration Resistance

LVC-5000-A Series is in compliance with MIL-STD-810G vibration and shock standards and includes SSD storage and a Suspension Kit to further improve robustness.

### Fanless Design with Corrugated Aluminum

The corrugated aluminum casing lets heat dissipate through the top of the device, allowing for a fanless design.

### Convenient DC output

The LVC-5000-A Series offers 12VDC output (max 1A) for external devices, operational in concert with the Ignition Power Management feature.

### Vehicle Ignition Power Management

Detects vehicle ignition on/off status and allows flexible control of the delay time via software utility.

## Analogue Video Grabber

The analogue solution is a high-quality, high-performance video capture device with on-board hardware H.264 compression engine can record live video from cameras into high-quality H.264 Baseline Profile files, which is specially designed for surveillance applications and supports up to 16 channels of video inputs and 1 channel of audio input.

## Key lock for Drive Bay

The system is with key lock for removable drive bay.







## Settings and Installation via the front panel

MCU setting and CF card and SIM card installation is easy to access simply by opening the front panel.

## Digital I/O

The Digital I/O design includes 12V Level DI/O, audio, MCU TX/RX and also includes 2x DI (Digital Input from MCU) which can connect sensors to detect the environment. Once defined events occur, the LVC-5000 series can be turned on automatically.

**Dimensions: 273.8 x 72 x 188 mm (10.78" x 2.84" x 7.4")**



# Preliminary Specifications

<b>Dimensions (WxHxD)</b>		273.8 x 72 x 188 mm (10.78" x 2.84" x 7.4" )
<b>Processor</b>		Intel® Celeron® 1047E
<b>Chipset</b>		Intel HM65
<b>System Memory</b>	Technology	DDR3 SO-DIMM x1 ( Factory default: 4GB module pre-installed )
	Max. Capacity	Up to 8GB
<b>Storage</b>	SATA/CF	Removable 2.5" SSD/HDD drive bay x1, CF socket x1
<b>Ethernet Controller</b>		Intel 82583V x4
<b>Graphic Controller</b>		Intel integrated HD graphic engine
<b>Audio Controller</b>		Realtek ALC886 HD codec
<b>IO</b>	LAN	GbE RJ45 x 4
	Display	DVI-D, maximum resolution up to 1920x1200@75Hz VGA, maximum resolution up to 2048x1536@60Hz HDMI, maximum resolution up to 1920x1200@75Hz
		Dual display supports Independent, clone and extended mode.
	Audio	Mic-in and Line-out with 2 watt by terminal block MIO connector
	Serial I/O	1x RS-232/422/485 both with RI/5V/12V
	GPS	Ublox NEO-7N GPS receiver module
	G-sensor	ADXL 345
	Digital I/O	4x DI and 4x DO with 5V/12V Level by jumper setting 2x DI (from MCU) 3.3V Level 2x DO control relay with contact current @ 2A
	USB 2.0	Type A x4
	Power Input	3-pin terminal block (+, -, ignition)
	Power Output	12 V / 1A DC
	Expansion	Mini-PCIe x2 (Both with SIM card slot)
	Video Grabber	Stretch S7100 H.264 Hardware En/Decoder without SDK supports for 16x Analogue Video Input, 1x Audio input
	PoE	N/A
	Others	External: 5x SMA antenna hole, Remote Power switch Internal: Lanner Proprietary DI/O
<b>Power Input</b>		+9~36VDC input range, with ignition delay on/off control
<b>PoE Power Module</b>		Internal integrated
<b>OS Support</b>		Linux: Redhat Enterprise 5/ Fedora 14. Linux Kernel 2.6.18 or later Windows: XP embedded ; Win7 Pro FES/Embedded; Win8
<b>Certifications</b>		CE, FCC Class A, E13, RoHS
<b>Compliance</b>		Vibration: MIL-STD-810G, Method 514.6 Shock: MIL-STD-810G, Method 516.6
<b>Operating Temperature Range</b>	Extended	With Selected Industrial Components: -20~55°C/-4~131°F
	Standard	With Commercial Components: -5~45°C / 23~113°F

## Ordering Information

LVC-5000-A2

Intel® Celeron 1047UE In-Vehicle Mobile DVR Computer, with 16Ch Video Input, 4GB DDR3 Memory included, 2.5" Removable Drive Bay, Mini-PCIe x2 with two SIM card reader, Intel GbE x4, USB x4, COM x2, DIO, Audio, Power input +9~36Vdc with Ignition, Suspension Kit included.