



## 200 Watts WR-90 RF Load Up To 12.4 GHz

# **TECHNICAL DATA SHEET**

**PE6833** 

### 200 Watts WR-90 RF Load Up To 12.4 GHz

Configuration

Connector WR-90 Heat Sink Aluminum

**Electrical Specifications** 

Frequency Range, GHz

Impedance, Ohms

Maximum VSWR

Maximum Input Power, Watts

8.2 to 12.4

1.1.1

200

## **Mechanical Specifications**

Size

 Length, in [mm]
 6 [152.4]

 Width/Dia., in [mm]
 3 [76.2]

 Height, in [mm]
 3 [76.2]

 Color
 Black

Connector

Type WR-90

Compliance Certifications (visit www.Pasternack.com for current document)

#### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

200 Watts WR-90 RF Load Up To 12.4 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 200 Watts WR-90 RF Load Up To 12.4 GHz PE6833

URL: http://www.pasternack.com/high-power-waveguide-termination-frequency-range-820-1240-ghz-pe6833-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# **PE6833 CAD Drawing** 200 Watts WR-90 RF Load Up To 12.4 GHz

