

## DFNWB3x2-08L-B Power Management MOSFETs-Schottky


### **CJHD3101F P-channel MOSFET and Schottky Barrier Diode**

#### FEATURES


- Both a MOSFET Chip and a Schottky Diode Ship in an Package.
- Leadless Package Provides Great Thermal Characteristics
- Independent Pinout to Each Device to Ease Circuit Design
- Trench P-Channel for Low On Resistance
- Ultra Low V<sub>F</sub> Schottky
- Pb-Free Package are Available

#### APPLICATIONS

- Li-Ion Battery Charging
- High Side DC-DC Conversion Circuits
- High Side Drive for Small Brushless DC Motors
- Power Management in Portable, Battery Powered Products



#### MARKING



#### MOSFET MAXIMUM RATINGS (Ta = 25°C unless otherwise noted)

Symbol	Parameter	Value	Units
V <sub>DSS</sub>	Drain-Source voltage	-20	V
V <sub>GS</sub>	Gate-Source Voltage	±8	V
I <sub>D</sub>	Continuous Drain Current	-3.2	A
I <sub>DM</sub>	Drain Current-Pulsed	-13	A
P <sub>D</sub>	Power Dissipation	1.1	W
T <sub>J</sub>	Junction Temperature	150	°C
T <sub>stg</sub>	Storage Temperature	-55-150	°C
R <sub>θJA</sub>	Thermal Resistance from Junction to Ambient	110	°C /W

#### SCHOTTKY DIODE MAXIMUM RATINGS(Ta= 25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V <sub>RRM</sub>	Peak repetitive reverse voltage	20	V
V <sub>R</sub>	DC Blocking voltage	20	V
I <sub>F</sub>	Average rectified forward current	2.2	A

**MOSFET ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)**

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = -250μA	-20			V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = -16V, V <sub>GS</sub> = 0V			-1	μA
Gate –Source leakage current	I <sub>GSS</sub>	V <sub>GS</sub> = ±8V, V <sub>DS</sub> = 0V			±100	nA
<b>On Characteristics (Note 1)</b>						
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = -250μA	-0.45		-1.5	V
Drain-Source On-Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> = -4.5V, I <sub>D</sub> = -3.2A			80	mΩ
		V <sub>GS</sub> = -2.5V, I <sub>D</sub> = -2.2A			110	mΩ
		V <sub>GS</sub> = -1.8V, I <sub>D</sub> = -1A			170	mΩ
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> = -10V, I <sub>D</sub> = -2.9A		8.0		S
<b>Dynamic Characteristics</b>						
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> = -10V, V <sub>GS</sub> = 0V, f = 1MHz		680		pF
Output Capacitance	C <sub>oss</sub>			100		pF
Reverse Transfer Capacitance	C <sub>rss</sub>			70		pF
Total Gate Charge	Q <sub>G(TOT)</sub>	V <sub>DS</sub> = -10V, I <sub>D</sub> = -3.2A, V <sub>GS</sub> = -4.5V		7.4		nC
Threshold gate charge	Q <sub>G(TH)</sub>			0.6		nC
Gate-Source Charge	Q <sub>GS</sub>			1.4		nC
Gate-Drain Charge	Q <sub>GD</sub>			2.5		nC
<b>Switching Characteristics(note 2)</b>						
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>GS</sub> = -4.5V V <sub>DD</sub> = -10V, I <sub>D</sub> = -3.2A, R <sub>G</sub> = 2.4Ω,		5.8		ns
Turn-On Rise Time	t <sub>r</sub>			11.7		ns
Turn-Off Delay Time	t <sub>d(off)</sub>			16		ns
Turn-Off Fall Time	t <sub>f</sub>			12.4		ns
<b>Drain-Source Diode Characteristics and Maximum Ratings</b>						
Forward Diode Voltage	V <sub>SD</sub>	V <sub>GS</sub> = 0V, I <sub>S</sub> = -2.5A			-1.2	V

1. Pulse Test: Pulse Width≤300μs, Duty Cycle≤2%.

2. Switching characteristics are independent of operating junction temperatures.

**SCHOTTKY DIODE ELECTRICAL CHARACTERISTICS (Ta= 25°C unless otherwise noted)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V <sub>F1</sub>		0.425			I <sub>F</sub> =0.1A
	V <sub>F2</sub>			0.575		I <sub>F</sub> =1A
Reverse current	I <sub>R1</sub>			1	μA	V <sub>R</sub> =10V
	I <sub>R2</sub>			5	μA	