

## FEATURES:

- Special Design Available
- Low Current Requirements
- High Light Output
- Easy Key Code

## ABSOLUTE MAXIMUM RATINGS, $T_a = 25^\circ\text{C}$

Reverse voltage per led chip.....	5.0 V
D.C Forward current per led chip.....	30 mA
Pulse current. ( 1.10 duty cycle , 0.1 ms pulse width) per led chip.....	100mA
Operating temperat. range.....	-25°C to + 85°C
Storage temperat. range.....	-25°C to + 100°C
Lead soldering temp. ....	260°C for 5 seconds

## ELECTRICAL / OPTICAL CHARACTERISTICS AT $T_a = 25^\circ\text{C}$

PART NUMBER	LED CHIP MATERIAL	LED CHIP EMITT. COLOR	SURFACE COLOR	SEGM. OR DOT COLOR	PEAK WAVE LENG. 20mA	FORWARD VOLTAGE Vf 20mA (V) TIP MAX	LUMIN. INTENS. 10 mA (mcd) TYP
OPM 2007HR2CGW	GaAsP GaP	HI RED	GRAY	WHITE	635	1.8 2.3	4.8
OPM 2007SR3CGW	GaAlAs GaAs	SUPER RED	GRAY	WHITE	660	1.8 2.4	12.0
OPM 2007G1CGW	GaP	GREEN	GRAY	WHITE	570	2.1 2.8	4.8
OPM 2007O2CGW	GaAsP GaP	ORANGE	GRAY	WHITE	630	2.0 2.8	4.8

\*SPECIFICATIONS ARE SUBJECT TO CHANGE

\*THE PN s ABOVE MEANS STANDART VERSION, (SURFACE GRAY AND WHITE SEGMENT).

NOTE: ALL DIMENSIONS ARE IN mm, TOLERANCE IS +/- 0.25mm, UNLESS OTHERWISE NOTED. THE SLOPE ANGLE OF ANY PIN MAY BE +/- 5.0 MAX.

## PACKAGE DIMENSIONS AND PIN FUNCTION

