

KR Electronics, Inc.

General Description


KR 2986 is a 320 MHz bandpass filter. The 1 dB bandwidth is 60 MHz minimum. The filter is group delay and amplitude equalized. Other center frequencies and bandwidths available. Please consult the factory.

Features

- 320 MHz Center Frequency
- 60 MHz min 1 dB Bandwidth
- Group Delay/Phase Equalized
- Elliptic Response
- SMA Connectors
- 50 Ω Source and Load


Typical Performance

Overall Response (10 dB/div)



Typical Performance

Passband Amplitude & Group Delay (1 dB/div & 5 nsec/div)



Overall Stopband to 1 GHz (10 dB/div)




KR Electronics 2986

Specifications

Parameter	Specification
Filter type	Bandpass
Center Frequency	320 MHz
Insertion Loss	< 5 dB (4 dB typical)
Minimum 1 dB Bandwidth	60 MHz
Attenuation 264 MHz	50 dB min
Attenuation 380 MHz	50 dB min
Source and Load	50 Ω

Physical Dimensions



Notes:

1. Dimensions in inches
2. Rectangular case
3. Also available in surface mount package 0.5" x 2.0" x 0.30"

KR Electronics, Inc.
91 Avenel Street
Avenel, NJ 07001

Web www.krfilters.com
Email sales@krfilters.com
Phone (732) 636-1900
Fax (732) 636-1982