

# DIGITRON SEMICONDUCTORS

EPS5 SERIES





TVS BIDIRECTIONAL, 5 TO 48V, 1000W

## MAXIMUM RATINGS

Characteristics		Value
Stand-off voltage		5 to 48V
Peak pulse power (8 x 20 microsec pulse)		1000W
Peak pulse power (1 millisecond pulse)		150W
Power continuous ( $T_L = 3/8"$ )		2.5W
Storage and operating temperature range		-65° to +175°C

## ELECTRICAL CHARACTERISTICS @25°C


Part number	Stand-off voltage $V_R$	Minimum breakdown voltage $B_{V(\min)} @ 1mA$	Maximum leakage current $I_R @ V_R$	Maximum peak current $I_P$	Maximum clamping voltage $V_C @ 10A$	Maximum temperature coefficient $B_V$
	V	V	μA	A	V	% / °C
EPS5	5	6.0	50	89.4	9.5	0.030
EPS8	8	9.0	2	62.1	13.7	0.040
EPS12	12	13.8	1	40.3	21.6	0.050
EPS15	15	16.7	1	33.9	26.0	0.055
EPS17	17	19.0	1	30.8	29.2	0.060
EPS24	24	28.4	1	22.0	43.2	0.070
EPS28	28	31.0	1	19.2	47.8	0.075
EPS33	33	36.8	1	16.4	56.7	0.080
EPS48	48	54.0	1	11.2	84.3	0.090



# DIGITRON SEMICONDUCTORS

EPS5 SERIES

TVS BI DIRECTIONAL, 5 TO 48V, 1000W



Dim	Inches		Millimeters	
	Min	Max	Min	Max
BD	-	0.095	-	2.413
BL	-	0.180	-	4.572
LD	0.028	0.032	0.711	0.813
LL	0.700	-	17.800	-

Available Non-RoHS (standard) or RoHS compliant (add PBF suffix).

Available as "HR" (high reliability) screened per MIL-PRF-19500, JANTX level. Add "HR" suffix to base part number.