CMLT491E

SURFACE MOUNT SILICON NPN TRANSISTOR



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMLT491E is an NPN Low V_{CE}(SAT) 1.0 Amp transistor, epoxy molded in a space saving SOT-563 surface mount package and designed for applications requiring a high current capability and low saturation voltages.

MARKING CODE: L49



SOT-563 CASE

MAXIMUM RATINGS: (T _A =25°C)	SYMBOL		UNITS
Collector-Base Voltage	V_{CBO}	80	V
Collector-Emitter Voltage	V_{CEO}	60	V
Emitter-Base Voltage	V_{EBO}	5.0	V
Continuous Collector Current	l _C	1.0	Α
Peak Collector Current	I _{CM}	2.0	Α
Continuous Base Current	Ι _Β	200	mA
Power Dissipation	P_{D}	250	mW
Operating and Storage Junction Temperature	T_J, T_stg	-65 to +150	°C
Thermal Resistance	Θ_{JA}	500	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I _{CBO}	V _{CB} =60V		100	nA
I _{EBO}	V _{EB} =4.0V		100	nA
BV _{CBO}	I _C =100μA	80		V
BV CEO	I _C =10mA	60		V
BV EBO	I _E =100μA	5.0		V
V _{CE(SAT)}	I _C =500mA, I _B =50mA		0.20	V
V _{CE(SAT)}	I _C =1.0A, I _B =100mA		0.40	V
V _{BE(SAT)}	I _C =1.0A, I _B =100mA		1.1	V
V _{BE(ON)}	V_{CE} =5.0V, I_{C} =1.0A		1.0	V
h _{FE}	V_{CE} =5.0V, I_{C} =1.0mA	200		
h _{FE}	V_{CE} =5.0V, I_{C} =500mA	200	600	
h _{FE}	V_{CE} =5.0V, I_{C} =1.0A	50		
h _{FE}	V_{CE} =5.0V, I_{C} =2.0A	15		
f _T	V_{CE} =10V, I_{C} =50mA, f=100MHz	150		MHz
C_{ob}	V _{CB} =10V, I _E =0, f=1.0MHz		10	pF


R5 (29-June 2015)


CMLT491E

SURFACE MOUNT SILICON NPN TRANSISTOR




SOT-563 CASE - MECHANICAL OUTLINE





PIN CONFIGURATION



DIMENSIONS						
	INCHES		MILLIMETERS			
SYMBOL	MIN	MAX	MIN	MAX		
Α	0.0027	0.007	0.07	0.18		
В	0.008		0.20			
С	0.017	0.024	0.45	0.60		
D	0.059	0.067	1.50	1.70		
Е	0.020		0.50			
F	0.059	0.067	1.50	1.70		
G	0.043	0.051	1.10	1.30		
Н	0.006	0.012	0.15	0.30		
SOT-563 (REV: R2)						

LEAD CODE:

- 1) Collector
- 2) Collector
- 3) Base
- 4) Emitter
- 5) Collector
- 6) Collector

Pins 1, 2, 5 and 6 are common.

MARKING CODE: L49

R5 (29-June 2015)

CMLT491E





SERVICES

- · Bonded Inventory
- · Custom Electrical Screening
- Custom Electrical Characteristic Curves
- SPICE Models
- Custom Packaging
- Package Base Options
- Custom Device Development/Multi Discrete Modules (MDM™)
- · Bare Die Available for Hybrid Applications

LIMITATIONS AND DAMAGES DISCLAIMER: In no event shall Central be liable for any collateral, indirect, punitive, incidental, consequential, or exemplary damages in connection with or arising out of a purchase order or contract or the use of products provided hereunder, regardless of whether Central has been advised of the possibility of such damages. Excluded damages shall include, but not be restricted to: cost of removal or reinstallation, rework, ancillary costs to the procurement of substitute products, loss of profits, loss of savings, loss of use, loss of data, or business interruption. No claim, suit, or action shall be brought against Central more than two (2) years after the related cause of action has occurred.

In no event shall Central's aggregate liability from any warranty, indemnity, or other obligation arising out of or in connection with a purchase order or contract, or any use of any Central product provided hereunder, exceed the total amount paid to Central for the specific products sold under a purchase order or contract with respect to which losses or damages are claimed. The existence of more than one (1) claim against the specific products sold to Buyer under a purchase order or contract shall not enlarge or extend this limit.

Buyer understands and agrees that the foregoing liability limitations are essential elements of a purchase order or contract and that in the absence of such limitations, the material and economic terms of the purchase order or contract would be substantially different.

R5 (29-June 2015)