

IFN5564, IFN5565, IFN5566

N-Channel Dual Silicon Junction Field-Effect Transistor

- Wide Band Differential Amplifier
- Commutators

Absolute maximum ratings at $T_A = 25^\circ\text{C}$.

Reverse Gate Source & Reverse Gate Drain Voltage	- 40 V
Continuous Forward Gate Current	50 mA
Continuous Device Power Dissipation	650 mW
Power Derating	3.3 mW/ $^\circ\text{C}$

At 25°C free air temperature:
Static Electrical Characteristics

		IFN5564		IFN5565		IFN5566		Process NJ72		
		Min	Max	Min	Max	Min	Max	Unit	Test Conditions	
Gate Source Breakdown Voltage	$V_{(\text{BR})\text{GSS}}$	- 40		- 40		- 40		V	$I_G = - 1 \mu\text{A}, V_{DS} = \emptyset\text{V}$	
Gate Leakage Voltage	I_{GSS}		- 100		- 100		- 100	pA	$V_{GS} = - 20\text{V}, V_{DS} = \emptyset\text{V}$	
			- 200		- 200		- 200	nA		$T_A = 150^\circ\text{C}$
Gate Source Cutoff Voltage	$V_{GS(\text{OFF})}$	- 0.5	- 3	- 0.5	- 3	- 0.5	- 3	V	$V_{DS} = 15\text{V}, I_D = 1 \text{nA}$	
Gate Source Voltage	$V_{GS(f)}$		1		1		1	V	$V_{DS} = \emptyset\text{V}, I_G = 2 \text{mA}$	
Saturation Current (Pulsed)	I_{DSS}	5	30	5	30	5	30	mA	$V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$	
Static Drain Source ON Resistance	$r_{DS(\text{ON})}$		100		100		100	Ω	$I_D = 1 \text{mA}, V_{GS} = \emptyset\text{V}$	

Dynamic Electrical Characteristics

Common Source Forward Transconductance	g_{fs}	7000	12500	7000	12500	7000	12500	μhmo	$V_{DG} = 15\text{V}, I_D = 2 \text{mA}$	$f = 1 \text{kHz}$
		7000		7000		7000		μhmo		$f = 100 \text{MHz}$
Common Source Output Transconductance	g_{os}		45		45		45	μhmo	$V_{DS} = 15\text{V}, I_D = 2 \text{mA}$	$f = 1 \text{kHz}$
Common Source Input Capacitance	C_{iss}		12		12		12	pF	$V_{DS} = 15\text{V}, I_D = 2 \text{mA}$	$f = 1 \text{MHz}$
Common Source Reverse Transfer Capacitance	C_{rss}		3		3		3	pF	$V_{DS} = 15\text{V}, I_D = 2 \text{mA}$	$f = 1 \text{MHz}$
Noise Figure	NF		1		1		1	dB	$V_{DS} = 15\text{V}, I_D = 2 \text{mA}$ $R_G = 1 \text{M}\Omega$	$f = 10 \text{Hz}$
Equivalent Short Circuit Input Noise Voltage	\bar{e}_N		50		50		50	$\text{nV}/\sqrt{\text{Hz}}$	$V_{DG} = 15\text{V}, I_D = 2 \text{mA}$	$f = 10 \text{Hz}$

Characteristics

Saturation Drain Current Ratio (Pulsed)		I_{DSS1}	0.95	1	0.95	1	0.95	1	-	$V_{DG} = 15\text{V}, V_{GS} = \emptyset\text{V}$	
		I_{DSS2}							-		
Differential Gate Source Voltage		$ V_{GS(1)} - V_{GS(2)} $		5		10		20	mV	$V_{DS} = 15\text{V}, I_D = 2 \text{mA}$	
Gate Source Voltage Differential Drift		$\Delta V_{GS(f)} - V_{GS(f)} $		10		25		50	$\mu\text{V}/^\circ\text{C}$	$V_{DS} = 15\text{V}, T_A = 25^\circ\text{C}$	$T_B = 125^\circ\text{C}$
		ΔT		10		25		50	$\mu\text{V}/^\circ\text{C}$	$I_D = 2 \text{mA}, T_A = 55^\circ\text{C}$	$T_B = 25^\circ\text{C}$
Transconductance Ratio (Pulsed)		$g_{fs(1)}$	0.95	1	0.9	1	0.9	1	-	$V_{DS} = 15\text{V}, I_D = 2 \text{mA}$	
		$g_{fs(2)}$							-		

TO-71 Package

Dimensions in Inches (mm)

Pin Configuration

1 Source, 2 Drain, 3 Gate, 4 Omitted,
5 Source, 6 Drain, 7 Gate, 8 Omitted