

FEATURES

- True double-conversion
- Microprocessor control optimizes reliability
- Input power factor correction
- **Output power factor 0.9**
- Wide input voltage (120 V – 300 V)
- Converter mode available
- ECO mode for energy saving
- Generator compatible
- Charger capacity expansion to 6A for long-run models
- Smart SNMP works well with either USB or RS-232 together
- Comprehensive display allows easy monitoring and access of UPS status

PRODUCT HIGHLIGHT

Wattage:	900W
Power Factor :	0.9
Input Range:	120-300 VAC ±5%

PHASE (ONLY FOR ONLINE UPS)

Phase:	1-phase in / 1-phase out
---------------	--------------------------

INPUT

Capacity:	1000 VA / 900 W
Voltage:	100/110/115/120/127VAC or 200/208/220/230/240VAC
Voltage Range:	120-300 VAC ±5%
Frequency Range:	(60/50 Hz (auto sensing))

OUTPUT

AC Voltage Regulation (Batt. Mode) :	± 1%
Frequency Range (Batt. Mode):	50 Hz or 60Hz ± 0.5%
Waveform (Batt. Mode):	Pure Sine Wave

BATTERY

Battery Type:	12 V / 9 AH
Battery Number:	2
Typical Recharge Time:	4 hours recover to 90% capacity



SAFETY STANDARD APPROVAL



PROTECTION

Full Protection:	Overload, Discharge, Overcharge, Protection
-------------------------	---

PHYSICAL

Output Receptacles:	India, French, Schuko, NEMA, and IEC selections
Dimension:	282mm(L) x 145mm(W) x 220mm(H)
Net Weight (kgs):	9.8

OPERATING ENVIRONMENT

Humidity:	20-90 % RH @ 0- 40°C (non-condensing)
Noise Level:	Less than 50dBA @ 1 Meter

MANAGEMENT

Optional USB/RS-232 Port:	Supports Windows 2000/2003/XP/Vista/2008/7/8, Linux, Unix, and MAC
----------------------------------	--

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice