

FEATURES

- **HIGH POWER**
 Pout=47.0dBm at Pin=42.0dBm
- **HIGH GAIN**
 GL=8.0dB at 13.75GHz to 14.5GHz
- **BROAD BAND INTERNALLY MATCHED HEMT**
 HERMETICALLY SEALED PACKAGE
- **LOW INTERMODULATION DISTORTION**
 IM3(Min.)=-25dBc at Po=40.0dBm
 Single Carrier Level

RF PERFORMANCE SPECIFICATIONS (Ta= 25°C)

CHARACTERISTICS	SYMBOL	CONDITIONS	UNIT	MIN.	TYP.	MAX.
Output Power	Pout	VDS = 24V IDSset=2.0A f = 13.75 to 14.5GHz @ Pin=42dBm	dBm	46.0	47.0	—
Gain Flatness	ΔG		dB	—	—	±0.8
Drain Current	IDS1		A	—	5.0	6.0
Power Added Efficiency	ηadd		%	—	29	—
Gate Current	IgRF		mA	-40	—	+100
Linear Gain	GL	@Pin=20dBm	dB	7.0	8.0	—
3rd Order Intermodulation Distortion	IM3	Two-Tone Test Po= 40.0dBm (Single Carrier Level)	dBc	-25	—	—
Drain Current	IDS2		A	—	5.0	6.0
Channel Temperature Rise	ΔTch	(VDS X IDS + Pin - Pout) X Rth(c-c)	°C	—	130	150

Recommended gate resistance(Rg) : Rg= 13.3 Ω (TYP.)


ELECTRICAL CHARACTERISTICS (Ta= 25°C)

CHARACTERISTICS	SYMBOL	CONDITIONS	UNIT	MIN.	TYP.	MAX.
Transconductance	gm	VDS= 5V IDS= 5.0A	S	—	4.5	—
Pinch-off Voltage	VGSoff	VDS= 5V IDS= 23mA	V	-1	-4	-6
Saturated Drain Current	IDSS	VDS= 5V VGS= 0V	A	—	15	—
Gate-Source Breakdown Voltage	VGSO	IGS= -10mA	V	-10	—	—
Thermal Resistance	Rth(c-c)	Channel to Case	°C/W	—	—	1.6

◆The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may results from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others. The information contained herein is subject to change without prior notice. It is therefore advisable to contact TOSHIBA before proceeding with design of equipment incorporating this product.

ABSOLUTE MAXIMUM RATINGS (Ta= 25°C)

CHARACTERISTICS	SYMBOL	UNIT	RATING
Drain-Source Voltage	VDS	V	50
Gate-Source Voltage	VGS	V	-10
Drain Current	IDS	A	15
Total Power Dissipation (Tc= 25 °C)	PT	W	140
Channel Temperature	Tch	°C	250
Storage	Tstg	°C	-65 to +175

PACKAGE OUTLINE (7- AA07A)**HANDLING PRECAUTIONS FOR PACKAGE MODEL**

Soldering iron should be grounded and the operating time should not exceed 10 seconds at 260°C.