


Metal Wire-wound Chip Power Inductors (MCOIL(TM) MB series)

MBKK1608TR24N



■ Features

- Item Summary
0.24 μ H(\pm 30%), 1650mA, 2300mA, 0603
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 3000pcs

■ Products characteristics table

CaseSize (EIA/JIS)	0603/1608
Inductance	0.24 μ H(\pm 30%)
Inductance Measuring Frequency	1MHz
Rated Current -Saturation Current	1650mA
Rated Current -Temperature Rise Current	2300mA
DC Resistance (max)	0.049 Ω
Avg. of DC.Resistance	0.043 Ω
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow


■ External Dimensions

L	1.6mm \pm 0.2
W	0.8mm \pm 0.2
H	1mm max

■ Recommended Land Patterns

【推奨ランドパターン】
実装上の注意
- 実装条件を確認の上で使用ください。お問い合わせいたします。
- 本製品のはんだ付けはリフローはんだ工法に限ります。

【Recommended Land Pattern】
Surface Mounting
* Mounting and soldering conditions should be checked beforehand.
* Applicable soldering process to these products is reflow soldering only.



Metal Wire-wound Chip Power Inductors (MCOIL_{TM}, MB series)

Type	A	B	C
1608	0.55	0.70	1.00
2012	0.60	1.00	1.45
2520	0.60	1.50	2.00

unit:mm

2015.02.25

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
Before making final selection, please check product specification.