

PRODUCT SUMMARY

SKY77615 Multimode Multiband Power Amplifier Module

Applications

- Quad-band cellular handsets:
- Class 4 GSM850/EGSM900
- Class 1 DCS1800/PCS1900
- Class E2 GSM850/EGSM900/ DCS1800/PCS1900
- Class 12 multi-slot EGPRS
- Multiband 3G
- WCDMA Bands: I, II, III, IV/X, V/VI, VIII

Features

- Hybrid PA architecture:
 - combined 2G / 3G input
- Internal switches configure inputs / outputs:
 Penta-band 3G outputs
- Design optimized for DC/DC converter use in all modes: 2.5G / 3G.
 - optimize transceiver / PA current by adjusting DC/DC Converter, PA bias current, and transceiver drive power
- Fully programmable Mobile Industry Processor Interface (MIPI) control
- MIPI programmable bias modes in conjunction with analog VBIAS control optimizes best efficiency/linearity trade-off for 2.5G and 3G; minimizes DG09 for 3G.
- Small, low profile package:
 - 6 mm x 8 mm x 0.9 mm
 - 36-pad configuration



Skyworks Green[™] products are compliant with all applicable legislation and are halogen-free. For additional information, refer to Skyworks *Definition of Green*[™], document number SQ04-0074.

Description

Skyworks SKY77615 is a hybrid multimode multiband (MMMB) Power Amplifier Module (PAM) that supports 2.5G / 3G handsets, and operates efficiently in GSM, EGPRS, EDGE, and WCDMA modes. The module is fully programmable through MIPI.

The PAM consists of a GSM850/EGSM900 PA block, a DCS1800/PCS1900 PA block, a separate WCDMA block for low and high bands, RF input/output ports internally matched to 50 ohms to reduce the number of external components, and a Multi-Function Control (MFC) block. A CMOS integrated circuit, using standard MIPI control, provides the internal MFC interface and operation. Extremely low leakage current maximizes handset standby time.

The InGaP die and the silicon die and passive components are mounted on a multilayer laminate substrate. The assembly is encapsulated in a 6 mm x 8 mm x 0.9 mm, 36-pad MCM, SMT package which allows for a highly manufacturable, low cost solution.

2.5G: The SKY77615 supports the GSM850, EGSM900, DCS1800, and PCS1900 bands as well as 2.5G Class 12 Enhanced General Packet Radio Service (EGPRS) multi-slot operation and EDGE linear modulation.

For both GMSK and EDGE modes, quiescent current is adjusted according to the output power target using the VBIAS pad in order to minimize current drain at each power level and output power is controlled by varying input power.

3G: The SKY77615 supports WCDMA, High-Speed Downlink Packet Access (HSDPA), and High Speed Uplink Packet Access (HSUPA) modulation. Varying the input power level provides output power control. VCC is adjusted using a DC/DC converter to maximize efficiency for each power level and modulation type.

3G Modulation scheme includes:

- WCDMA Voice Release 99
- HSPA+
- HSUPA
- HSDPA categories

Ordering Information

Product Name	Order Number	Evaluation Board Part Number
SKY77615 Multimode Multiband Power Amplifier Module	SKY77615	

Copyright © 2013, Skyworks Solutions Inc. All Rights Reserved.

formation in this document is provided in connection with Skyworks Solutions Inc. ("Skyworks") products or services. These materials including t	he information contained herein are provided by
kyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for	errors or omissions in these materials or the
formation contained herein. Skyworks may change its documentation products services specifications or product descriptions at any time withou	t notice. Skyworks makes no commitment to
odate the materials or information and shall have no responsibility whatsoever for conflicts incompatibilities or other difficulties arising from any f	uture changes.

No license whether express implied by estoppel or otherwise is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials products or information provided hereunder including the sale distribution reproduction or use of Skyworks products information or materials except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND WHETHER EXPRESS IMPLIED STATUTORY OR OTHERWISE INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE MERCHANTABILITY PERFORMANCE QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT, ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION TEXT GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES INCLUDING BUT NOT LIMITED TO ANY SPECIAL INDIRECT INCIDENTAL STATUTORY OR CONSEQUENTIAL DAMAGES INCLUDING WITHOUT LIMITATION LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical lifesaving or life-sustaining applications or other equipment in which the failure of the Skyworks products could lead to personal injury death physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products which may deviate from published specifications as a result of design defects errors or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance customer product design or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks the Skyworks symbol "Breakthrough Simplicity" DCR Helios HIP3 Innovation to Go Intera iPAC LIPA Polar Loop and System Smart are trademarks or registered trademarks of Skyworks Solutions Inc. in the United States and other countries. Third-party brands and names are for identification purposes only and are the property of their respective owners. Additional information including relevant terms and conditions posted at www.skyworksinc.com are incorporated by reference.