



# Series X508 Single and Dual Row Collet Sockets with Wire Wrap Pins

## FEATURES:

- Aries collet sockets are available in single or dual rows.
- Cuttable to the number of pins desired to fit the application.
- Side-to-side and end-to-end stackable.

## SPECIFICATIONS:

- Body material is black UL 94V-0 Nylon 4/6.
- Pin body is Brass Alloy 360 1/2 hard per UNS C36000 ASTM-B16-00.
- Pin body plating is either 10  $\mu$  [.25 $\mu$ m] min. Gold per MIL-G-45204 or 200 $\mu$  [5.08 $\mu$ m] min. 93/7 Tin/Lead per ASTM B545 or 200 $\mu$  [5.08 $\mu$ m] min. Tin per ASTM B545 Type 1 over 100 $\mu$  [2.54 $\mu$ m] min. Nickel per SAE-AMS-QQ-N-290.
- 4-fingered collet contact is Beryllium Copper Alloy per UNS C17200 ASTM-B194-01.
- Contact plating is either 200 $\mu$  [5.08 $\mu$ m] min. 93/7 Tin/Lead per ASTM B545 or 200 $\mu$  [5.08 $\mu$ m] min. Tin per ASTM B545 Type 1 or 10 $\mu$  [.25 $\mu$ m] min. Gold per MIL-G-45204 over 50 $\mu$  [1.27 $\mu$ m] min. Nickel per SAE-AMS-QQ-N-290.
- Contact current rating=3 Amps.
- Operating Temp. = -67°F to 221°F [-55°C to 105°C] Tin  
= -67°F to 257°F [-55°C to 125°C] Gold
- Insertion Force=180 grams/pin; Withdrawal Force=90 grams/pin;  
Normal Force=140 grams/pin; based on a .018 [.46] dia. test lead.
- Accepts leads .015-.025 [.38-.64] in diameter, .110-.160 [2.79-4.06] long.


## MOUNTING CONSIDERATIONS:

- Suggested PCB hole size=.045  $\pm$  .002 [1.14  $\pm$  .05] dia.

## ALL DIMENSIONS: INCHES [MILLIMETERS]

"A"=(NO. OF PINS PER ROW) X .100 [2.54]

"B"=(NO. OF PINS PER ROW - 1) X .100 [2.54]




All tolerances  $\pm$  .005 [.13] unless otherwise specified




Note: Aries specializes in custom design and production. In addition to the standard products shown on this page, special materials, platings, sizes, and configurations can be furnished, depending on quantities. Aries reserves the right to change product specifications without notice.

## ORDERING INFORMATION



Consult Data Sheet No. 12020 for Series X518 Collet Sockets with solder tail pins.



**ARIES**  
ELECTRONICS, INC.  
http://www.arieselec.com • info@arieselec.com

NORTH AMERICA  
Bristol, PA USA  
TEL: (215) 781-9956  
FAX: (215) 781-9845



EUROPE  
TEL: +44 870 240 0249  
FAX: +44 871 919 6033  
europe@arieselec.com



12021  
REV. F

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Aries:

[20-0508-20](#) [11-0511-10](#) [11-0511-11](#) [10-0511-11](#) [10-0511-10](#) [52-1508-30](#) [52-1508-31](#) [52-1508-20](#) [52-1508-21](#)  
[56-1508-21](#) [56-1508-20](#) [56-1508-31](#) [56-1508-30](#) [54-1508-31](#) [54-1508-30](#) [54-1508-21](#) [54-1508-20](#) [50-1508-30](#) [58-](#)  
[1508-20](#) [50-1508-31](#) [58-1508-21](#) [50-1508-20](#) [58-1508-30](#) [58-1508-31](#) [50-1508-21](#) [10-1508-30](#) [18-1508-20](#) [10-](#)  
[0508-30](#) [18-0508-20](#) [10-0508-31](#) [18-0508-21](#) [10-1508-31](#) [18-1508-21](#) [18-1508-30](#) [10-0508-20](#) [18-0508-30](#) [18-](#)  
[1508-31](#) [18-0508-31](#) [10-0508-21](#) [14-0508-21](#) [14-1508-21](#) [14-1508-20](#) [14-0508-20](#) [14-1508-31](#) [14-0508-31](#) [14-](#)  
[0508-30](#) [14-1508-30](#) [12-0508-21](#) [12-1508-21](#) [12-1508-20](#) [12-0508-20](#) [12-1508-31](#) [12-0508-31](#) [12-0508-30](#) [12-](#)  
[1508-30](#) [16-1508-30](#) [16-0508-30](#) [16-1508-31](#) [16-0508-31](#) [16-0508-20](#) [16-1508-20](#) [16-1508-21](#) [16-0508-21](#) [17-](#)  
[0508-20](#) [17-0508-21](#) [17-0508-30](#) [17-0508-31](#) [13-0508-21](#) [13-0508-20](#) [13-0508-31](#) [13-0508-30](#) [19-0508-21](#) [11-](#)  
[0508-31](#) [11-0508-30](#) [19-0508-20](#) [19-0508-31](#) [11-0508-21](#) [19-0508-30](#) [11-0508-20](#) [15-0508-20](#) [15-0508-21](#) [15-](#)  
[0508-30](#) [15-0508-31](#) [29-0505-20](#) [60-1508-31](#) [60-1508-30](#) [60-1508-21](#) [60-1508-20](#) [09-0511-11](#) [09-0511-10](#) [05-](#)  
[0511-10](#) [05-0511-11](#) [03-0511-11](#) [03-0511-10](#) [07-0511-10](#) [07-0511-11](#) [04-0511-11](#) [04-0511-10](#) [08-0511-10](#) [08-](#)  
[0511-11](#)